Canon

Canon PowerShot A1200 1/2.3" Cámara compacta 12.1 MP CCD 4000 x 3000 Pixeles Negro

Marca : Canon Familia de productos: Código del producto: PowerShot 5032B001

Nombre del producto: A1200

12.1MP, 4000×3000 , 1/2.3" CCD, DIGIC 4+iSAPS, f/2.8 - f/5.9, 2.7" TFT, 4x óptico zoom, USB 2.0, A/V output, PAL/NTSC, PictBridge, 185g

Canon PowerShot A1200. Tipo de cámara: Cámara compacta, Megapixeles: 12.1 MP, Tamaño del sensor de imagen: 1/2.3", Tipo de sensor: CCD, Máxima resolución de imagen: 4000 x 3000 Pixeles. Zoom óptico: 4x, Zoom digital: 4x, Intervalo de longitud focal: 5 - 20 mm. Tipo HD: HD, Máxima resolución de video: 1280 x 720 Pixeles. Diagonal de la pantalla: 6.86 cm (2.7"). Tipo de visor de imagen: Óptico. PictBridge. Peso: 185 g. Color del producto: Negro



Picture quality		Viewfinder	
Image sensor size *	1/2.3" Compact camera	Viewfinder type	Optical
Megapixel (approx.) * 12.1 N		Ports & interfaces	
	12.1 MP CCD	PictBridge *	✓
Sensor type * Maximum image resolution *	4000 x 3000 pixels	USB version *	2.0
Image stabilizer *	X	Camera	
Lens system		White balance *	Auto, Cloudy, Custom modes, Daylight, Fluorescent, Tungsten
Optical zoom * Digital zoom * Focal length range Lens structure (elements/groups)	4x 4x 5 - 20 mm 7/6	Scene modes * Photo effects * Camera playback	Beach, Children, Fireworks, Portrait, Snow, Landscape Black&White, Neutral, Sepia, Vivid Movie, Single image
Combined zoom	16x	Playback zoom (max)	2x
Filter Number of aspheric elements	Primary Colour 1	Languages support	Arabic, Czech, English, Japanese, Korean, Ukrainian
Focusing		Custom colour	✓
Focus *	TTL	Histogram	✓
Focus adjustment *	Auto	Image editing	Resizing
,	Centre weighted Auto Focus, Continuous Auto Focus, Multi Point Auto Focus, Single Auto Focus	Image processor	DIGIC 4 iSAPS
Auto focusing (AF) modes *		Design	
Face tracking	✓	Product colour *	Black
Closest focusing distance	0.03 m	Battery	
Auto Focus (AF) lock	✓	Battery technology *	Nickel-Metal Hydride (NiMH)
Auto Focus (AF) assist beam	✓	Battery life (CIPA standard)	200 shots
Exposure		Battery type	AA
ISO sensitivity	80, 100, 200, 400, 800, 1600, Auto Centre-weighted, Spot	System requirements	
Light metering *		Mac compatibility	✓
Flash		Operational conditions	
Flash modes *	Auto, Flash off, Manual, Slow synchronization	Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 10 - 90%
Flash exposure lock	✓	Weight & dimensions	
Flash range (wide)	0.3 - 4 m	Width	97.5 mm
Flash range (tele)	0.5 - 2 m	Depth	30.7 mm
Video		Height	62.5 mm
Video recording * Maximum video resolution * HD type *	✓ 1280 x 720 pixels HD	Weight	185 g

Video		Packaging content	
Motion JPEG frame rate Video formats supported	30 fps MOV	Bundled software	ZoomBrowser EX / ImageBrowser PhotoStitch
Memory		Other features	
Compatible memory cards *	MMC, SD, SDHC, SDXC	Video capability	✓
Display		Interface	USB 2.0 (Mini-B), Video out (PAL/ NTSC)
Display *	LCD	Data compression	Fine, Normal
Touchscreen *	×	Built-in flash	✓
Display diagonal *	6.86 cm (2.7")	Camera shutter speed	1 - 1/1600 s
Display resolution (numeric)	230000 pixels 100%	Focal length (35mm film equivalent)	28 - 112 mm
Field of view		Compatible operating systems	Windows 7/ Vista SP1-2/ XP SP3 Mac OS X v10.5 - 10.6
		Digital SLR	×
		Video memory capacity	4GB (HD)/10 min.

