

Intellinet 24-Port Gestionado Negro



Marca : Intellinet

Código del producto: 523554

Nombre del producto : 24-Port

Intellinet 24-Port. Tipo de interruptor: Gestionado. Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 24, Puerto de consola: RS-232. Bidireccional completo (Full duplex). Tabla de direcciones MAC: 8192 entradas, Capacidad de conmutación: 48 Gbit/s. Montaje en rack

Management features		Performance	
Switch type *	Managed	Firmware upgradeable	✓
Quality of Service (QoS) support	✓	Power	
Web-based management	✓	Power source *	AC
Ports & interfaces		Redundant power supply (RPS) support	✗
Basic switching RJ-45 Ethernet ports quantity *	24	Number of power supply units	1
Gigabit Ethernet (copper) ports quantity	4	Input voltage	100 - 240 V
Combo SFP ports quantity	4	Power consumption (typical)	22.1 W
SFP/SFP+ slots quantity	4	Power over Ethernet (PoE)	
Console port	RS-232	Power over Ethernet (PoE) *	✗
Network		Other features	
10G support *	✗	Slot type	SFP
Copper ethernet cabling technology	1000BASE-T, 100BASE-TX, 10BASE-T	Dimensions (WxDxH)	441 x 130 x 44 mm
Port mirroring	✓	Connectivity technology	Wired
Full duplex	✓	Expansion slots	4 SFP Module Slots
Broadcast storm control	✓	Packet transfer speed	1488000 pps
Number of VLANs	24	Mounting interface	19" / 1U
Data transmission		Wi-Fi	✗
Supported data transfer rates	10/100/1000 Mbps	Power LED	✓
Switching capacity *	48 Gbit/s	Connectivity LEDs	✓
MAC address table *	8192 entries	Size (imperial)	48.3 cm (19")
Store-and-forward	✓	Weight (imperial)	2.45 kg (5.4 lbs)
Number of static routes	24	Input frequency	50 - 60 Hz
Maximum data transfer rate	1 Gbit/s	Networking connector	RJ45
Jumbo frames support	✓	Dimensions (W x D x H) (imperial)	442 x 129.5 x 43.2 mm (17.4 x 5.1 x 1.7")
Packet buffer memory	0.512 MB	Cable length	1 m
Security		Operational conditions	
MAC address filtering	✓	Operating temperature (T-T)	0 - 40 °C
Design		Operating relative humidity (H-H)	10 - 90%
Rack mounting *	✓	Storage relative humidity (H-H)	-10 - 80%
Product colour	Black	Weight & dimensions	
		Weight	2.5 kg

Design		Packaging content	
Housing material	SECC	Cables included	AC, Serial
LED indicators	LAN, Power, Status, Yes	Certificates	
Performance		Certification	FCC A, CE, VCCI A, RoHS
Media types supported	10Base-T Cat3, 4, 5 UTP/STP RJ-45 - 100Base-TX Cat5 UTP/STP RJ-45 - 1000Base-T Cat5e UTP/STP RJ-45		



0766623523554



766623523554



7666235235544



0766623560658



766623560658

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.