ASUS RAMPAGE V EXTREME Intel® X99 LGA 2011-v3 ATX extendida

Marca: ASUS Código del producto: 90MB0JG0-M0AAY0

Nombre del producto : RAMPAGE V EXTREME

E-ATX, Intel X99 Express Chipset, 8 x DDR4 DIMM, ROG SupremeFX, 4 x PCI Express x16 (x16), 1 x PCI Express x16 (x4), 1 x PCI Express x1, Gigabit LAN,, Wi-Fi 802.11a/b/g/n/ac, CrossFire/SLI, SATA3, USB 3 0/2 0

ASUS RAMPAGE V EXTREME. Fabricante de procesador: Intel, Socket de procesador: LGA 2011-v3, Procesador compatible: Intel® Core™ i7. tipos de memoria compatibles: DDR4-SDRAM, Memoria interna máxima: 64 GB, Tipo de ranuras de memoria: DIMM. Interfaces de disco de almacenamiento soportados: SATA, SATA II, SATA III, Niveles RAID: 0, 1, 5, 10. Soporte para proceso paralelo: 2-Way CrossFireX, 2-Way SLI, 3-Way CrossFireX, 3-Way SLI, 4-Way CrossFireX, 4-Way SLI. Controlador LAN: Intel® I218-V, Estándares de Wi-Fi: 802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)





Processor		Rear panel I/O ports	
Processor manufacturer *	Intel	Ethernet LAN (RJ-45) ports *	1
Processor socket *	LGA 2011-v3	PS/2 ports quantity	1
Compatible processor series *	Intel® Core™ i7	Microphone in	✓
Memory		S/PDIF out port	✓
Supported memory types *	DDR4-SDRAM	Network	
Number of memory slots *	8	Ethernet LAN	✓
Memory slots type	DIMM	LAN controller	Intel® I218-V
Memory channels	Quad-channel	Wi-Fi *	✓
Supported memory clock speeds	2133,2400,2666,2800,3000,3300 MHz	Wi-Fi standards	802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)
Maximum internal memory *	64 GB	Bluetooth	V
Storage controllers		Bluetooth version	4.0
Supported storage drive interfaces * RAID levels	SATA, SATA II, SATA III 0, 1, 5, 10	Features	
	3, 2, 3, 23	Motherboard chipset *	Intel® X99
Graphics		Audio output channels *	7.1 channels
Parallel processing technology support *	2-Way CrossFireX, 2-Way SLI, 3-Way CrossFireX, 3-Way SLI, 4-Way CrossFireX, 4-Way SLI	Component for *	PC
		Motherboard form factor *	Extended ATX
Internal I/O		Motherboard chipset family *	Intel
	2	Power source type	ATX
USB 2.0 connectors *	2	Expansion slots	
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	2	PCI Express x1 slots	1
Number of SATA III connectors *	8	PCI Express x16 slots	5
Number of SATA connectors	8	BIOS	
Front panel audio connector	✓	BIOS type *	UEFI
ATX Power connector (24-pin)	✓	BIOS memory size	256 Mbit
CPU fan connector	✓	ACPI version	5.0
Rear panel I/O ports		Clear CMOS button	✓
USB 2.0 ports quantity *	2		
F 1: - 7			

Rear panel I/O ports	Weight & dimensions	Weight & dimensions	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	Width Depth	305 mm 272 mm	
	Other features		
	BIOS switch button	1	
	Back-to-BIOS button	✓	

