

Samsung DM32D Pantalla plana de señalización digital 81.3 cm (32") LED Wifi 450 cd / m² Full HD Negro

Marca : Samsung

Código del producto: LH32DMDPLGA/ZA

Nombre del producto : DM32D



Samsung DM32D. Diseño de producto: Pantalla plana de señalización digital. Diagonal de la pantalla: 81.3 cm (32"), Tecnología de visualización: LED, Resolución de la pantalla: 1920 x 1080 Píxeles, Brillo de pantalla: 450 cd / m², Tipo HD: Full HD. Wifi. Color del producto: Negro



Display		Performance	
LED backlighting type	Direct-LED	TV tuner integrated	✓
Display diagonal *	81.3 cm (32")	Ambient light sensor	✓
Display technology *	LED	Power	
Display resolution *	1920 x 1080 pixels	Power consumption (typical) *	61 W
Display brightness *	450 cd/m²	Power consumption (standby) *	0.5 W
HD type *	Full HD	AC input voltage	100 - 240 V
Touchscreen *	✗	AC input frequency	50 - 60 Hz
Native aspect ratio	16:9	Computer system	
Response time	8 ms	Computer system *	✓
Contrast ratio (typical)	5000:1	Computer system type	Thin client
Viewing angle, horizontal	178°	Processor family	ARM Cortex
Viewing angle, vertical	178°	Processor model	Cortex-A9
Supported graphics resolutions	1920 x 1080 (HD 1080)	Processor frequency	1 GHz
Supported video modes	1080p	Internal memory	1.5 GB
Ports & interfaces		Internal storage capacity	4 GB
HDMI ports quantity *	1	Weight & dimensions	
HDMI input ports quantity	1	Width	721.4 mm
DVI port *	✓	Depth	50.8 mm
DVI-D ports quantity	1	Height	419.1 mm
VGA (D-Sub) input ports	1	Weight	4.85 kg
DisplayPorts quantity *	2	Packaging data	
DisplayPorts out	1	Package width	800.1 mm
DisplayPort version	1.2	Package depth	116.8 mm
USB ports quantity	1	Package height	469.9 mm
USB version	2.0	Package weight	5.9 kg
Ethernet LAN *	✓	Packaging content	
Ethernet LAN (RJ-45) ports	1	Remote control included	✓
Wi-Fi *	✓	Batteries included	✓
Composite video in	1	Cables included	AC, VGA
Component video (YPbPr/YCbCr) in	1		
RS-232C	✓		

Audio		Operational conditions	
Built-in speaker(s) *	✓	Operating temperature (T-T)	0 - 40 °C
Design		Operating relative humidity (H-H)	10 - 80%
Product design *	Digital signage flat panel	Technical details	
Product colour *	Black	Sustainability certificates	ENERGY STAR
VESA mounting *	✓	Compliance certificates	RoHS
Panel mounting interface	200 x 200 mm	Other features	
		Manual	✓
		Quick start guide	✓
		Number of products included	1 pc(s)

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date