

ASUS X99-PRO placa base Intel® X99 LGA 2011-v3 ATX

Marca : ASUS

Código del producto: X99-PRO

Nombre del producto : X99-PRO

ASUS X99-PRO. Fabricante de procesador: Intel, Socket de procesador: LGA 2011-v3, Procesador compatible: Intel® Core™ i7. tipos de memoria compatibles: DDR4-SDRAM, Memoria interna máxima: 64 GB, Tipo de ranuras de memoria: DIMM. Interfaces de disco de almacenamiento soportados: SATA, Niveles RAID: 0, 1, 5, 10. Soporte para proceso paralelo: 3-Way CrossFireX, 3-Way SLI, Quad-GPU CrossFireX, Quad-GPU SLI. Tipo de interfaz ethernet: Gigabit Ethernet, Controlador LAN: Intel® I218-V, Estándares de Wi-Fi: 802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)



Processor		Rear panel I/O ports	
Processor manufacturer *	Intel	USB 2.0 ports quantity *	4
Processor socket *	LGA 2011-v3	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	6
Compatible processor series *	Intel® Core™ i7	Ethernet LAN (RJ-45) ports *	1
Memory		PS/2 ports quantity	1
Supported memory types *	DDR4-SDRAM	Headphone outputs	5
Number of memory slots *	8	Microphone in	✓
Memory slots type	DIMM	S/PDIF out port	✓
Memory channels	Quad-channel	Thunderbolt ports quantity	1
ECC compatibility	Non-ECC	Network	
Supported memory clock speeds	2133 MHz	Ethernet LAN	✓
Maximum internal memory *	64 GB	Ethernet interface type	Gigabit Ethernet
Unbuffered memory	✓	LAN controller	Intel® I218-V
Storage controllers		Wi-Fi *	✓
Supported storage drive interfaces * SATA		Wi-Fi standards	802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)
RAID levels	0, 1, 5, 10	Bluetooth	✓
Graphics		Bluetooth version	4.0
Parallel processing technology support *	3-Way CrossFireX, 3-Way SLI, Quad-GPU CrossFireX, Quad-GPU SLI	Features	
Internal I/O		Motherboard chipset *	Intel® X99
USB 2.0 connectors *	2	Audio chip	Realtek ALC1150
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	2	Component for *	PC
Number of SATA connectors	8	Motherboard form factor *	ATX
ATX Power connector (24-pin)	✓	Motherboard chipset family *	Intel
CPU fan connector	✓	Power source type	ATX
Number of chassis fan connectors	4	Expansion slots	
Chassis intrusion connector	✓	PCI Express x16 (Gen 3.x) slots	3

Internal I/O		BIOS	
EPS power connector (8-pin)	✓	BIOS type *	UEFI
Number of COM connectors	1	Weight & dimensions	
TPM connector	✓	Width	305 mm
		Depth	244 mm
		Packaging content	
		Cables included	SATA

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date