



P8A46-S70	
ASPECTOS GENERALES	
Tipo de Entorno	Básico / Escolar / Oficina / Hogar
Sistema Operativo	Sin S.O.
GABINETE	
Tipo	Medio Torre
Ranuras de Expansión	6
Factor de forma soportado	ATX
Soporte para GPU	31.5 cm
Bahías Internas	1 x 3.5 2 x 2.5
Bahías Externas	Ninguna
Pantallas Frontales	Ninguna
Ventiladores	1x Ventilador Trasero
Dimensiones	330 x 175 x 405 mm
Color	Negro / Iluminación RGB
PROCESADOR	
Línea	A-Series
Modelo	5600
Socket	AM4
Arquitectura	Branch Ridge
Núcleos	4
Hechos	6
Velocidad Base reloj	3.1 GHz
Max boost Clock	3.4 GHz
Cache L2	2 MB
Desbloqueo	BI
CMOS	28nm
Cóculos	Radeon R7 Series
Graphics Frequency	900 MHz
TDP	45 / 65W
TARJETA MADRE	
Factor de Forma	Micro ATX
Socket	AMD AM4 Socket for AMD Ryzen™ 7th Generation A-series/Ribbon™ Processors
Chipset	AMD X300
Memoria Ram	2 x DIMM Max. 32GB, DDR4 3200VO C.J2933D C.J0960/4000/2133 MHz, ECC and non-ECC, Un-buffered Memory 2 x DIMM Max. 32GB, DDR4 2400V1133 MHz Non-ECC, Un-buffered Memory
Soporte Multi-GPU	Dual Channel Memory Architecture Multi-VGA output support - HDMI/RGB ports
Chipset de Audio	Realtek® ALC887 8-Channel High Definition Audio CODEC
Puertos de Almacenamiento	4 x SATA 6Gb/s ports, SATA Support RAID 0, 1, 10 1 x M.2 Socket 3, with M key, type 2242/2260/2280 storage devices support (SATA mode) 1 x M.2 Socket 3, with M key, type 2242/2260/2280 storage devices support (NVMe mode)
Puertos de Expansión	1 x PCIe 3.0 x16 (x16 mode) 1 x PCIe 3.0 x2 (x16 mode) 2 x PCIe 2.0 x1
Puertos del Panel Trasero	1 x PS/2 keyboard (purple) 1 x PS/2 mouse (green) 1 x D-Sub 1 x HDMI 1 x LAN (RJ45) ports 4 x USB 3.1 Gen 1 (Blue) 2 x USB 2.0 2 x Audio (jack)
Capacidades Especiales	ASUS DX Protection III ASUS SafeSlot Core: Fortified PCIe Slot prevents damage ASUS LANGuard: Protects against LAN surges, lightning strikes and static electricity discharges ASUS Overvoltage Protection: World-class circuit protecting power design ASUS Stainless-Steel Back I/O: 3X corrosion-resistance for greater durability ASUS Extreme Features: - AI Suite 3 - AI Charger ASUS Quiet Thermal Solution - Stylish Fanless Design Heat sink solution - ASUS Fan Xpert ASUS EZ DIY - ASUS CoolLine BIOS 3 - ASUS EZ Flash 3 - ASUS UEFI BIOS EZ Mode - Multi-language BIOS ASUS Q-Design - ASUS Q-Slot - ASUS Q-DIMM
DISCO DURO	
Capacidad	1TB
Distribución	1 x 1TB
Velocidad	7200 rpm
Cache	32 MB
Interfaz	SATA
Factor de forma	3.5"
Transferencia de datos	60Gbps
Latencia	4.1ms
Peso	-
MEMORIA RAM	
Tipo	DDR4
Densidad Total	8GB
Distribución	1X 8GB
Frecuencia	3400 MHz
Latencia CAS	14
Formato	288-Pin
Configuración	Dual Channel
Voltage	1.2 volts
Enfriamiento	HeatSink
Uso	PC/ Servidor
TARJETA DE VIDEO	
Motor Gráfico	RX 570
Chipset	OpenCL 4.5
Memoria de Video	4GB
Bus	PCI Express 3.0
Frecuencia de reloj	1310 MHz (OC Mode) 1300 MHz (Default Mode)
Memory Clock	7000 MHz
Interfaz de Memoria	256-bit
Resolución	5120x2880 DVI Output: Yes x 2 (Native) (DVI-D) HDMI Output: Yes x 1 (Native) (HDMI 2.0) Display Port: Yes x 1 (Native) (Regular DP) HDCP Support: Yes
FUENTE DE PODER	
Potencia	600w
Certificación	N/A
Ventilación	12 cm
KIT TECLADO / MOUSE	
Teclado	
Interfaz	Usb / Plug & Play
Iluminación	4 grados de iluminación Múltiples colores retroiluminación
Protecciones	Electro-resistencia A prueba de derrame de líquido Función anti-ghost
Longitud Cable	170cm
Mouse	
Interfaz	Usb / Plug & Play
Iluminación	Iluminación LED Múltiples Colores
Tipo seguimiento	Sensor Óptico
DPI	Ajustable 800-1000-1600-2400-3200DPI
Longitud Cable	170cm
Requisitos Sistema	Windows 10/ Vista/ 7/ 10/Mac os/ en mac las funciones multimedia se pueden perder