



MODELO	ENS-PA12P6
DESCRIPCION	PATCH PANEL CAT5E 12PUERTOS ENSON ENS-PA12P6

NOTES:

ELECTRICAL:

- 1. VOLTAGE RATING : 125 VAC RMS
- 2. CURRENT RATING : 1.5 AMP
- 3. CONTACT RESISTANCE : 100 MILLIOHMS MAX
- 4. INSULATION RESISTANCE : 1000 MEGOHMS MIN @ 500 VDC
- 5. DIELECTRIC STRENGTH : 750 VAC RMS 60Hz,1MIN

ENVIRONMENTAL:

- 1. STORAGE : -40° TO +70°
- 2. OPERATION : -10° TO +60°

CONFORM TO TIA/EIA 568B CATEGORY 5e

MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68,

MECHANICAL:

- 1. HOUSING MATERIAL : PBT
- 2. PANEL FRAME : ST12, POWDER COATING IN BLACK COLOR
- 3. IDC MATERIAL : PC UL94V-0 TERMINAL-PHOSPHOR BRONZE, TIN PLATING
- 4. RJ45 JACK LIFE : 750 TIMES MIN
- 5. IDC LIFE : 200 TIMES MIN
- 6. WIRE : AWG 22~24

7. TIA Cat.6 Perm. Link Test: Worst pair NEXT margin ≥ 3.0 dB

8. Retentiveness of insertion structure: 50N 60 \pm 5s

