



LMR BATTERY SPECIFICATIONS	PART NUMBER
	BP4409LIIC

COMPATIBLE RADIOS	Motorola APX1000, APX2000, APX3000, APX4000, XPR3300, XPR3300e, XPR3500, XPR3500e, XPR7350, XPR7350e, XPR7550, XPR7550e, XPR7580, XPR7580e, DP4400, DP4401, DP4600, DP4601, DP4800, DP4801
REPLACES OEM BATTERY	PMNN4409
COMPATIBLE CHARGERS	Endura EC1-MT16A, EC1M-MT16A, TWC2M-MT16-D, EC6M-MT16A, TWC12M-MT16-D / Logic LEVCA-MT16 / Motorola IMPRES WPLN4222, PMPN4284
VOLTAGE	7.4V
CAPACITY	2500 mAh / 18.5 Wh
CHEMISTRY / CELL TYPE	Li-Ion / Panasonic or equivalent
BATTERY TYPE	Smart
OPERATING TEMPERATURE	-10° C to +60° C (discharge) / 0° C to +40° C (charge)
CHARGE CYCLES	450
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Yes
THERMAL PROTECTION	Yes
HOUSING MATERIAL / SEAL	ABS / ultrasonic weld
RATING	IP67
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	Available (CL7144)
WARRANTY	12 months
PRODUCT PHOTO	 BP4409LIIC shown with available belt clip (CL7144).

ESPECIFICACIONES DE BATERIA RECARGABLE	PARTE NUMERO
	BP4409LIIC

Compatible con radios:	Motorola APX1000, APX2000, APX3000, APX4000, XPR3300, XPR3300e, XPR3500, XPR3500e, XPR7350, XPR7350e, XPR7550, XPR7550e, XPR7580, XPR7580e, DP4400, DP4401, DP4600, DP4601, DP4800, DP4801
Reemplaza baterías :	PMNN4409
Compatible con cargadores :	Endura EC1-MT16A, EC1M-MT16A, TWC2M-MT16-D, EC6M-MT16A, TWC12M-MT16-D / Logic LEVCA-MT16, entre otros
Voltaje:	7.4V
Capacidad:	2500 mAh / 18.5 Wh
Tipo de celda (composición química):	ión- Li / fabricadas por Panasonic o equivalente
Tecnología:	Sistema de energía inteligente (Smart)
Temperatura de operación:	-10° C to +60° C (descarga) / 0° C to +40° C (carga)
Ciclos de carga:	>400 ciclos
Ciclos de trabajo:	5-5-90/10.5 h
Tiempo de operación:	10.5 h
Peso:	152 g
Dimensiones:	115 x 52 x 23 mm
Tipo de carga :	rápida
Acondicionador compatible:	SI
Protección térmica:	SI
Mat.recubrimiento/sellado:	ABS/soldado por ultrasonido
Clasificación estándar:	IP67
Metal de soldadura:	Níquel puro / suelda de punto
Clip:	Disponible
Garantía:	12 meses
Foto del producto:	