

## BATTERY with INTERNAL CHARGER SPECIFICATIONS

## PART # PC232

ORIGINAL EQUIPMENT MANUFACTURER	ICOM	
EQUIPMENT MODELS ORIGINAL EQUIPMENT	F14/F24/F40/F43/F43TR/3021/4021	PAYE & PC232  MECHANISHABLE LADIN BAFFERY 7-4V / 2800-MAN / 19.24 WH PORT SCORE PSI, GC-2812 AG-2827  PARE SCORE PSI, GC-2812 AG-2812  PROPERTY OF THE ACCOUNTY OF THE ACCOUNT
BATTERY PART(S)	BP232	
CHEMISTRY	Li-Ion	
VOLTAGE	7.5V	
CAPACITY	2600 mAh	
BATTERY CELL TYPE	Gold Peak or Equivalent	
CHARGE TYPE	Rapid	
OPERATING TEMPERATURES	0 to 50 Degrees Celsius	
THERMAL PROTECTION	Yes	
EXTERIOR CASE COMPOSITION	ABS	
CASE SEAL	Ultrasonic	
INTERNAL COMPONENT CELL ASSEMBLY	Pure nickel tabs with spot welding	
INTERNAL COMPONENT CHARGER ASSEMBLY	5V to 7.5V Internal inverter powered by micro- USB mated to charging circuit and status LED	
- CHARGER ASSEMBLY	(red to green)	
BELT CLIP	N/A	
WARRANTY	12 Months	IMAGE

Positive Charge 2617 Blue Mound Rd. W Suite 1180 Haslet, TX 76052 817-929-9506

web: www.positive-charge.biz