



## BP72V60ART2U EBM

The Extended Battery Module offers extended run-times during power outages.

The CyberPower BP72V60ART2U (72V) Extended Battery Module (EBM) with Fast Charge Technology provides extended battery run-time during power outages for select Smart App Online UPS models. Up to 10 EBMs can be added and fast charging times are maintained thanks to each EBM having a built in battery charger. The typical charging times of 4 hours for the OL2200RTXL2U, OL3000RTXL2U, and OL3000RTXL2UHV are maintained whether there are 1 or 10 EBMs installed..

Each EBM takes up 2U of rack space and can also be installed in a tower form factor to match the UPS. A DC plug-n-play power connector makes it easy to daisy-chain additional EBMs to a UPS system.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material and workmanship.

### Compatible Applications

- OL2200RTXL2U
- OL3000RTXL2U
- OL3000RTXL2UHV

### Features

- 72V / 60A Output
- Fast Charge Technology
- Daisy-chain Power Connections
- Expandable Battery Modules
- Plug-n-Play DC Connectors
- 2U Rack/Tower Form Factor
- 3-Year Warranty

# BP72V60ART2U EBM

The Extended Battery Module offers extended run-times during power outages.

GENERAL	
Voltage	72V
Amperage	60A
BATTERY	
Battery Type	Sealed Lead-Acid
Battery Size	12V/9Ah
Battery Quantity	12
Hot-Swappable	Yes
User Replaceable	Yes
Replacement Battery Cartridge	RB1290X6B
Replacement Battery Cartridge Quantity	2
Typical Recharge Time	4 hours
Built-in Charger	Yes
Expansion Ready (Daisy-Chain)	Yes
PHYSICAL	
Rack Size	2U
Enclosure Construction	Steel
Mounting Hardware	Included
Dimensions - W×H×D (in)	17 × 3.5 × 23.6 inches
Dimensions - W×H×D (mm)	590 × 214.1 × 890 mm
Weight (lbs)	96.8 lbs
Weight (kg)	43.9 kg
Shipping Dimensions - W×H×D (in)	23.23 × 8.43 × 35.04 inches
Shipping Weight (lbs)	115.94 lbs
Shipping Weight (kg)	52.6 kg
ENVIRONMENTAL	
Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Humidity	0 - 90% (non-condensing)
Operating Elevation	0 - 10,000 ft (0 - 3,000 m)
Storage Temperature	5 - 113 °F (-15 - 45 °C)
Storage Relative Humidity	0 - 95% (non-condensing)
Storage Elevation	0 - 50,000 ft (0 - 15,000 m)
CERTIFICATIONS	
Safety	UL1778, CSA C22.2 NO.107.3-05, FCC DOC Class A
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	3 Years Limited