



RE305

CARACTERÍSTICAS DE HARDWARE

Tipo de Enchufe	EU, UK, US
Estándares y Protocolos	IEEE802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11a, IEEE 802.11b
Interface	1 x 10/100M Ethernet Port (RJ45)
Botón	WPS Button, Reset Button
Consumo de Energía	7.3W (max power consumption)
Dimensiones (W X D X H)	3.1 x 3.0 x 3.0 in. (80 x 78 x 77mm)
Antena	2 x external

CARACTERÍSTICAS INALÁMBRICAS

Frecuencia	2.4GHz & 5GHz(11ac)
Tasa de Señal	5GHz:Up to 867Mbps 2.4GHz:Up to 300Mbps



CARACTERÍSTICAS INALÁMBRICAS

Sensibilidad de Recepción	5GHz : 11a 6Mbps:-91dBm@10% PER 11a 54Mbps: -74dBm@10% PER 11ac HT20 mcs8: -68dBm@10% PER 11ac HT40 mcs9: -63dBm@10% PER 11ac HT80 mcs9: -59dBm@10% PER 2.4GHz 11g 54M: -79dBm@10% PER 11n HT20 mcs7: -77dBm@10% PER 11n HT40 mcs7: -74dBm@10% PER
Modos Inalámbricos	Range Extender/Access Point Wireless Statistic Concurrent Mode boost both 2.4G/5G Wi-Fi band
Funciones Inalámbricas	Wireless Statistic Concurrent Mode boost both 2.4G/5G Wi-Fi band Access Control LED Control Domain Login Function
Seguridad Inalámbrica	64/128-bit WEP WPA-PSK / WPA2-PSK
Potencia de Transmisión	<17dBm(2.4GHz) <17dBm(5GHz)



OTHERS

Certification	CE, FCC, RoHS
Package Contents	AC1200 Wi-Fi Range Extender RE305 Quick Installation Guide
Box Dimensions (W X D X H)	6.15 x 4 x 3.7 in. (156.5 x 101.5 x 95mm)
System Requirements	Microsoft® Windows® 98SE, NT, 2000, XP, Vista or Windows 7, 8, 10, Mac® OS, NetWare®, UNIX® or Linux.
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing