QNAP

QNAP TS-h1886XU-RP R2 NAS Bastidor (2U) Intel® Xeon® D D-1622 32 GB DDR4 0 TB QuTS hero Negro

Marca: QNAP Código del producto: TS-H1886XU-RP-R2-

D1622-32G-US

Nombre del producto: TS-h1886XU-RP R2

QNAP TS-h1886XU-RP R2. Tipo: NAS. Tipo de chasis: Bastidor (2U). Clase del dispositivo: Grandes empresas. Familia de procesador: Intel® Xeon® D, Modelo del procesador: D-1622, Frecuencia del procesador: 2.6 GHz. Memoria interna: 32 GB, Tipo de memoria interna: DDR4. Capacidad de almacenamiento total instalado: 0 TB. Sistema operativo instalado: QuTS hero





Storage		Performance	
Storage drive capacity * Supported storage drive interfaces Storage drive sizes supported RAID support * RAID levels Online RAID migration Online RAID expansion RAID rebuild Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives supported	0 GB Serial ATA II, Serial ATA III 2.5,3.5" 0, 1, 5, 6, 10, 50, 60, JBOD FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4 0 TB	Backup features Buzzer Multilingual support Snapshot Management protocols Web-based management Security algorithms Access Control List (ACL) Reset button On/off switch Built-in FTP server Browser supported	Cloud, iSCSI LUN
* Installed storage drive type * Supported storage drive types * Disk roaming Processor	× HDD & SSD ✓	System log Hot spare S.M.A.R.T. support Software	* * *
Processor Processor manufacturer * Processor family * Processor model * Processor frequency * Processor boost frequency Processor cores Processor cache CPU configuration (max)	Intel Intel® Xeon® D D-1622 2.6 GHz 3.2 GHz 4 6 MB	Operating system installed * Operating system version Windows operating systems supported Linux operating systems supported Mac operating systems supported Server operating systems supported	QuTS hero h5.0.0 Windows 10, Windows 11, Windows 7, Windows 8 Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Convertigation
Memory Internal memory * Internal memory type	32 GB DDR4	Other operating systems supported Power	Server 2019 ✓
Maximum RAM supported Memory slots Memory form factor ECC Flash memory	128 GB 4 UDIMM ✓ 5000 MB	Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support	Built-in 550 W 2 ✓

Network		Power	
Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported (max)	100,1000,2500 Mbit/s 10000 Mbit/s	Power consumption (typical) AC input voltage Fan voltage	117.92 W 100 - 240 V 12 V
		Weight & dimensions	
DHCP client DHCP server Jumbo frames support iSCSI support		Width * Depth * Height * Weight	482 mm 549.7 mm 88.3 mm 12.7 kg
Wake-on-LAN ready	✓	Package weight	18.7 kg
Dynamic DNS (DDNS)	✓	Packaging content	
Ports & interfaces USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A	✓	Cables included Power cables quantity Number of screws	AC, LAN (RJ-45) 2 112
ports quantity	2	Processor special features	
Fiber ports quantity Fiber optic connector Ethernet LAN (RJ-45) ports * PCI Express x4 (Gen 3.x) slots PCI Express x8 (Gen 3.x) slots	2 SFP+ 4 1	Embedded options available Enhanced Intel SpeedStep Technology Execute Disable Bit	× ✓
Design		Idle States	/
Chassis type * Cooling type * Product colour Number of fans Fan diameter LED indicators	Rack (2U) Active Black 3 fan(s) 6 cm HDD, LAN, SSD, Status	Intel 64 Intel QuickAssist Technology Intel Trusted Execution Technology Intel TSX-NI Intel Virtualization Technology (VT-x) Intel Virtualization Technology for	×
Performance		Directed I/O (VT-d)	•
Type * NAS	NAS Large Enterprise Business	Intel VT-x with Extended Page Tables (EPT)	/
	•	Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H)	0 - 40 °C 5 - 95% -20 - 70 °C 5 - 95%

