



## TP-Link EAP620 HD V3.2 punto de acceso inalámbrico 1800 Mbit/s Blanco Energía sobre Ethernet (PoE)

**Marca :** TP-Link

**Código del producto:** EAP620 HD V3.2

**Nombre del producto :** EAP620 HD V3.2

TP-Link EAP620 HD V3.2. 2.4 GHz, 5 GHz, Rango máximo de transferencia de datos: 1800 Mbit/s. Algoritmos de seguridad: SNMP, SNMPv2, SNMPv3, SSH, WEP, WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPA3, WPA3-PSK. Ethernet LAN, velocidad de transferencia de datos: 10,100,1000 Mbit/s. Energía sobre Ethernet (PoE). Color del producto: Blanco



Features		Ports & interfaces	
2.4 GHz *	✓	DC-in jack	✓
5 GHz *	✓	<b>Power</b>	
Maximum data transfer rate *	1800 Mbit/s	Power over Ethernet (PoE) *	✓
Maximum data transfer rate (2.4 GHz)	574 Mbit/s	Output voltage	12 V
Maximum data transfer rate (5 GHz)	1201 Mbit/s	<b>Design</b>	
Ethernet LAN data rates	10,100,1000 Mbit/s	Placement *	Ceiling, Wall
Frequency band	2.4 - 5 GHz	Product colour *	White
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3at	Reset button	✓
		<b>Antenna</b>	
MIMO	✓	Antenna type *	Internal
MIMO type	Multi User MIMO	Antenna direction type	Omni-directional
Modulation	1024-QAM, OFDM	Antenna gain level (max)	6 dBi
Wi-Fi Multimedia (WMM)/(WME)	✓	<b>Performance</b>	
VLAN support	✓	Compatible operating systems	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Linux
Virtual LAN features	VLAN mapping	<b>Certificates</b>	
Rate limiting	✓	Certification	CE, FCC, RoHS
Band steering	✓	<b>Weight &amp; dimensions</b>	
Quality of Service (QoS) support	✓	Width	160 mm
Transmitting power (CE)	20/23 dBm	Depth	160 mm
Transmitting power (FCC)	23 dBm	Height	33.6 mm
<b>Security</b>		<b>Packaging data</b>	
Security algorithms *	SNMP, SNMPv2, SNMPv3, SSH, WEP, WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPA3, WPA3-PSK	Package type	Box

Security		Packaging content	
Service Set Identifier (SSID) features	Multiple SSIDs	Quantity per pack	1 pc(s)
Number of SSID supported	16	AC adapter included	✓
Management features		Quick start guide	✓
		Operational conditions	
Web-based management	✓	Operating relative humidity (H-H)	10 - 90%
Syslog	✓	Operating temperature (T-T)	0 - 40 °C
Firmware upgradeable	✓	Storage temperature (T-T)	-40 - 70 °C
Ports & interfaces		Storage relative humidity (H-H)	5 - 90%
Ethernet LAN (RJ-45) ports *	1		



4897098680315

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date