

Lenovo ThinkSystem SR250 V2 servidor 0 GB Bastidor (1U) Intel Xeon E E-2286G 4 GHz 16 GB DDR4-SDRAM 450 W

Marca : LenovoFamilia de productos:
ThinkSystemCódigo del producto:
7D7Q1000LA

Nombre del producto: SR250

V2

Lenovo ThinkSystem SR250 V2. Familia de procesador: Intel Xeon E, Frecuencia del procesador: 4 GHz, Modelo del procesador: E-2286G. Memoria interna: 16 GB, Tipo de memoria interna: DDR4-SDRAM, Diseño de memoria (ranuras x tamaño): 1×16 GB. Capacidad total de almacenaje: 0 GB. Ethernet, Tecnología de cableado: 10/100/1000Base-T(X). Fuente de alimentación: 450 W, Suministro de energía redundante (RPS), soporte. Tipo de chasis: Bastidor (1U)

Processor		Performance	
Processor family *	Intel Intel Xeon E E-2286G	Trusted Platform Module (TPM) Trusted Platform Module (TPM) version	2.0
Processor frequency *	4 GHz	Software	
Processor boost frequency	4.9 GHz	Operating system installed *	×
Processor cache 12 MB Motherboard chipset Intel C256 Number of processors installed 1	Intel C256	Compatible operating systems *	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi
Execute Disable Bit	/	Processor special features	
Idle States	/	CPU configuration (max)	1
Embedded options available	×	Enhanced Intel SpeedStep Technology	✓
Memory Internal memory *	16 GB	Intel Virtualization Technology for Directed I/O (VT-d)	✓
Internal memory type *	DDR4-SDRAM	Intel Trusted Execution Technology	✓
Memory slots ECC	4x DIMM ×	Intel VT-x with Extended Page Tables (EPT)	✓
Memory layout (slots x size)	1 x 16 GB	Intel TSX-NI	✓
Maximum internal memory *	128 GB	Intel Clear Video Technology	✓
Storage		Intel Software Guard Extensions (Intel SGX)	✓
Total storage capacity *	0 GB	Intel 64	✓
RAID support * Supported RAID controllers	✓ 5350-8i	Intel Virtualization Technology (VT-x)	✓
Hot-swap	✓	Power	
Optical drive type *	×	Redundant power supply (RPS)	
Internal drive bays	8	support *	✓
Graphics		Power supply *	450 W
On-board graphics card	✓	Number of redundant power supplies supported	2
On-board graphics card model	Intel UHD Graphics P630	Number of main power supplies	1
Network		Operational conditions	
LAN controller	Broadcom 5719	Operating temperature (T-T)	5 - 45 °C
Ethernet LAN	✓	Storage temperature (T-T)	-40 - 60 °C
Cabling technology	10/100/1000Base-T(X)	Operating relative humidity (H-H)	8 - 90%
Ethernet interface type	Gigabit Ethernet	Storage relative humidity (H-H)	8 - 90%
Ports & interfaces		Operating altitude	0 - 3050 m
Ethernet LAN (RJ-45) ports *	4	Weight & dimensions	
USB 2.0 ports quantity	1	Width	435 mm

Ports & interfaces		Weight & dimensions	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Depth Height	545 mm 43 mm
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2	Weight	12.3 kg
VGA (D-Sub) ports quantity	1		
Serial ports quantity	1		
Design			
Chassis type *	Rack (1U)		
Product colour	Black, Metallic		
Rack mounting	✓		

