
## Kodak S3140 MAX Escáner con alimentador automático de documentos (ADF) 600 x 600 DPI A3 Negro, Blanco

Marca : Kodak Alaris Familia de productos: Kodak Código del producto:

8009441

Nombre del producto: S3140

MAX





Scanning		Network	
Maximum scan size * Optical scanning resolution *	305 x 457 mm 600 x 600 DPI	Ethernet LAN Supported network protocols	✓ TCP/IP, DHCP
Colour scanning	<b>✓</b>	Power	
Input colour depth Output colour depth Output greyscale depth ADF scan speed (b/w, A4)	48 bit 24 bit 8 bit 140 ppm	Power supply type * AC input frequency Input voltage	AC 50 - 60 Hz 100 - 240 V
Duplex ADF scan speed (b/w, A4)	280 ipm	Weight & dimensions	
Design		Width	457.2 mm
Scanner type * Product colour * Display	ADF scanner Black, White LCD	Depth Height Weight	370.8 mm 295 mm 16.5 kg
Display diagonal	8.89 cm (3.5")	Sustainability	
Touchscreen	✓	Sustainability certificates	ENERGY STAR, EPEAT Gold
Colour display	✓	System requirements	
Built-in display *	<b>/</b>	Windows operating systems supported	Windows 10, Windows 11
Performance		Linux operating systems supported	Ubuntu 18.04 LTS, Ubuntu 20.04
Sensor type * Light source Scan file formats Daily duty cycle (max) *	Dual CIS RGB LED BMP, JPEG, PDF, PNG, RTF, TIFF 50000 pages		LTS Windows Server 2012 R2 x64, Windows Server 2016 x64, Windows Server 2019, Windows Server 2022
Scan drivers	ISIS, Kofax VRS, SANE, TWAIN, WIA	Operational conditions	
Scanning noise level	66 dB	Operating temperature (T-T) Operating relative humidity (H-H)	10 - 35 °C 15 - 80%
Input capacity Standard input capacity	500 sheets	Other features	
	Jou sileets		INTEL CORE i3, running @ 3.5 GHz
Paper handling  Maximum ISO A-series paper size *  Auto Document Feeder (ADF) media	A3	Recommended system requirements	or higher, USB port 3.0 (Super Speed) or 2.0 (High Speed), 3.43 GB RAM or more
weight	27 - 433 g/m²	Ethernet LAN data rates	10,100,1000 Mbit/s
Ports & interfaces		Minimum scan size	63.5 mm x 71.1 mm
USB port * USB version	✓ 3.2 Gen 1 (3.1 Gen 1)	Certification	S mark, RCM, cTUVus & ICES-003, CCC, CE, GS Mark, BIS, VCCI, NOM, EAC, KC, BSMI, cTUVus & FCC
USB connector type	USB Type-A	Technical details	
		Linear (1D) barcodes supported	Codabar, Code 128, Code 3 of 9, EAN-13, EAN-8, Interleaved 2 of 5, PDF417, UPC-A, UPC-E





041778009444

0041778009444

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.