



## Bosch NTI-40012-A3S cámara de vigilancia Bala (forma) Cámara de seguridad IP Interior y exterior 1280 x 960 Píxeles Techo/pared



**Marca :** Bosch

**Código del producto:** NTI-40012-A3S

**Nombre del producto :** NTI-40012-A3S

Bosch NTI-40012-A3S. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared, Color del producto: Blanco, Factor de forma: Bala (forma). Ángulo de visión del objetivo, horizontal: 32 - 100°, Ángulo de visión del objetivo, vertical: 18 - 53°, Tipo de disparador de la cámara: Electrónico. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.9 mm (1 / 2.9"). Intervalo de longitud focal: 2.8 - mm

Performance		Video	
Type *	IP security camera	Maximum resolution *	1280 x 960 pixels
Placement supported *	Indoor & outdoor	Total megapixels *	1 MP
Connectivity technology *	Wired	Noise reduction	✓
PTZ control	✓	Privacy masking	✓
Day/night mode	✓	Network	
Design		Ethernet LAN *	✓
Form factor *	Bullet	Ethernet interface type	Fast Ethernet
Mounting type *	Ceiling/wall	IPv4, IPv6, UDP, TCP, HTTP, HTTPS, RTP/RTCP, IGMP V2/V3, ICMP, ICMPv6, RTSP, FTP, ARP, DHCP, APIPA (Auto-IP, link local address), NTP (SNTP), SNMP (V1, V3, MIB-II), 802.1x, DNS, DNSv6, DDNS (DynDNS.org, selfHOST.de, no-ip.com), SMTP, iSCSI, UPnP (SSDP), DiffServ (QoS), LLDP, SOAP, Dropbox™, CHAP, digest authentication	
Product colour *	White		
International Protection (IP) code	IP66		
IK code	IK08		
Camera		Supported network protocols	
Camera pan control	✓	Wi-Fi *	✗
Camera tilt control	✓	Bluetooth *	✗
Lens viewing angle, horizontal	32 - 100°	Storage	
Lens viewing angle, vertical	18 - 53°	Built-in HDD *	✗
Camera shutter type	Electronic	Security	
Camera shutter speed	1/25 - 1/15000 s	Pixel counter	✓
Image sensor		Power	
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")	Power source type *	AC, DC, PoE
Sensor type *	CMOS	AC input voltage	24 V
Lens system		DC output voltage	12
Focal length range	2.8 - mm	Operational conditions	
Night vision		Operating temperature (T-T)	-30 - 60 °C
Night vision *	✓	Storage temperature (T-T)	-30 - 70 °C
Night vision distance	30 m	Operating relative humidity (H-H)	20 - 90%
LED type	IR	Weight & dimensions	
Number of illumination LEDs	4	Width	90 mm
		Depth	90 mm
		Height	271 mm
		Weight	1.3 kg
		Packaging content	
		Number of cameras *	1

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date