



Dahua Technology WizSense DH-IPC-HFW3441E-(A)S-S2 cámara de vigilancia Bala (forma) Cámara de seguridad IP Interior y exterior 2688 x 1520 Pixeles Techo/pared/Tubo



Marca : Dahua Technology

Familia de productos: WizSense

Código del producto: DH-IPC-HFW3441E-(A)S-S2

Nombre del producto : DH-IPC-HFW3441E-(A)S-S2

Dahua Technology WizSense DH-IPC-HFW3441E-(A)S-S2. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared/Tubo, Color del producto: Blanco, Factor de forma: Bala (forma). Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 107°, Ángulo de visión del objetivo, vertical: 56°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 3 mm (1 / 3"), Número de píxeles efectivos (A x V): 2688 x 1520 Pixeles. Distancia de detección: 63.6 m, Distancia de observación: 25.4 m, Distancia de reconocimiento: 12.7 m

Performance		Video	
Type *	IP security camera	Back Light Compensation (BLC)	✓
Placement supported *	Indoor & outdoor	Highlight Compensation (HLC)	✓
Connectivity technology *	Wired	Region of Interest (ROI) encoding	✓
Wide Dynamic Range (WDR)	✓	Audio	
Day/night mode	✓	Audio input channels	1 channels
Alarm input/output	✓	Audio output channels	1 channels
Luminous flux	0 lm	Signal-to-Noise Ratio (SNR)	56 dB
Dynamic range	120 dB	Built-in microphone	✓
Certification	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; FCC:47 CFR FCC Part 15, Subpart B; UL/CUL: UL62368-1 & CAN/CSA C22.2 No. 62368-1-14	Voice codecs	G.711Mu, G.711a, G.723, G.726, PCM
		Bit rate range	3 - 8192 Kbit/s
Design		Network	
Form factor *	Bullet	Ethernet LAN *	✓
Mounting type *	Ceiling/Wall/Pole	Ethernet interface type	Fast Ethernet
Product colour *	White	Supported network protocols	IPv4; IPv6; HTTP;TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; SNMP
Housing material	Metal		
International Protection (IP) code	IP67	Wi-Fi *	✗
Camera		Bluetooth *	✗
Angle of rotation	360°	Number of users	20 user(s)
Lens viewing angle, horizontal	107°	Client interoperability	ONVIF (Profile S/Profile G/Profile T); CGI; P2P; Milestone; Genetec
Lens viewing angle, vertical	56°	Storage	
Lens viewing angle, diagonal	127°	Built-in HDD *	✗
Tilt angle range	0 - 90°	Card reader integrated	✓
Pan range	0 - 360°	Compatible memory cards	MicroSD (TransFlash)
White balance	Auto, Manual, Natural, Outdoor, Regional custom, Street lamp	Internal memory	512 MB
Camera shutter speed	1/3 - 1/100000 s	ROM capacity	128 MB
Adjustment shutter speed	Auto/Manual	Ports & interfaces	
Number of Privacy masking areas	4	Ethernet LAN (RJ-45) ports	1
Image sensor		Security	
Optical sensor size	25.4 / 3 mm (1 / 3")	Alarm input channels	1
Progressive scan	✓	Alarm output channels	1
Sensor type *	CMOS	Video motion detection	✓
Number of effective pixels (H x V)	2688 x 1520 pixels	Intelligent Video Surveillance (IVS) system features	Intrusion, Tripwire
Lens system			
Detect distance	63.6 m		

Lens system		Security	
Observe distance	25.4 m	Mirror	✓
Recognize distance	12.7 m	Management features	
Focal length range	2.8 mm	Web-based management	✓
Identify distance	6.4 m	Management software	Smart PSS; DSS; DMSS
Closest focusing distance	0.7 m	Power	
Night vision		Power source type *	DC, PoE
Night vision *	✓	Power consumption (typical)	3.8 W
Night vision distance	50 m	Power consumption (max)	7.2 W
LED type	IR	Power consumption (Power over Ethernet (PoE))	5.9 W
Number of illumination LEDs	1	DC output voltage	12
Video		Operational conditions	
Maximum resolution *	2688 x 1520 pixels	Operating temperature (T-T)	-40 - 60 °C
Total megapixels *	4 MP	Storage temperature (T-T)	-40 - 60 °C
Video formats supported	H.264+, H.265+	Operating relative humidity (H-H)	0 - 95%
Video compression formats	H.264, H.264B, H.264H, H.265	System requirements	
Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2048 x 1536 (QXGA), 2304 x 1296, 2560 x 1440, 2688 x 1520	Mobile operating systems supported	Android, iOS
Frame rate	30 fps	Weight & dimensions	
Noise reduction	✓	Width	70.5 mm
Noise reduction technology	3D noise reduction	Depth	192.7 mm
Gain control type	Auto	Height	66.4 mm
Privacy masking	✓	Weight	590 g
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)	Packaging data	
		Package weight	780 g
		Packaging content	
		Number of cameras *	1
		Other features	
		Browser supported	IE: IE11 Chrome Firefox
		Technical details	
		Number of video streams	3

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date