

Allied Telesis GS950/18PS-V2 Gestionado Gigabit Ethernet (10/100/1000) Energía sobre Ethernet (PoE) Gris

Marca : Allied Telesis

Código del producto: AT-GS950/18PS-V2-40

Nombre del producto : GS950/18PS-V2



Allied Telesis GS950/18PS-V2. Tipo de interruptor: Gestionado. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 16. Capacidad de conmutación: 36 Gbit/s. Estándares de red: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE.... Conector eléctrico: Toma de entrada de CC. Energía sobre Ethernet (PoE). Montaje de pared, Montaje en rack

Management features		Security	
Switch type *	Managed	IGMP snooping	✓
Web-based management	✓	MAC address filtering	✓
System event log	✓	Multicast features	
Ports & interfaces		Multicast support	✓
Basic switching RJ-45 Ethernet ports quantity *	16	Design	
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Rack mounting *	✓
SFP module slots quantity	2	Product colour	Grey
Power connector	DC-in jack	Wall mountable	✓
Network		Power over Ethernet (PoE)	
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power over Ethernet (PoE) *	✓
		Power over Ethernet plus (PoE+) ports quantity	16
10G support *	✗	Operational conditions	
Port mirroring	✓	Operating temperature (T-T)	0 - 40 °C
Flow control support	✓	Storage temperature (T-T)	-25 - 70 °C
Link aggregation	✓	Operating relative humidity (H-H)	5 - 90%
Broadcast storm control	✓	Storage relative humidity (H-H)	5 - 95%
Rate limiting	✓	Weight & dimensions	
VLAN support	✓	Width	440 mm
Number of VLANs	256	Depth	250 mm
Data transmission		Height	44 mm
Switching capacity *	36 Gbit/s	Weight	3.7 kg
Throughput	26.78 Mpps	Packaging content	
Packet buffer memory	1.5 MB	Cables included	AC
Security			
DHCP features	DHCP client		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date