
HiLook DVR-208G-K1(S) videograbadora digital Negro

Marca: HiLook Código del producto: DVR-208G-K1(S)

Nombre del producto: DVR-208G-K1(S)





| Performance | | Network | |
|--|--|---|---|
| Maximum video resolution | 1920 x 1080 pixels | Ethernet LAN (RJ-45) ports | 1 |
| Video compression formats | H.264, H.264+, H.265, H.265 Pro, H.265 Pro+ | Supported network protocols | TCP/IP, PPPoE, DHCP, HiLookVision, DNS, DDNS, NTP, SADP, SMTP, NFS, |
| Audio formats supported | G.711 μ-law | | iSCSI, UPnP™, HTTPS |
| Playback resolutions supported | 1920×1080 1280×1024 1280×720 1024×768 | Number of users Hard drive | 128 user(s) |
| Product colour * | Black | 110100 01110 | |
| Plug and Play | ✓ | Number of HDDs supported HDD interface | 1 SATA |
| Audio input channels | 8 channels | Maximum HDD capacity | 4 TB |
| Audio output channels | 1.0 channels | Power | |
| Ports & interfaces | | | D.C. |
| Video input channels BNC input ports | 8 channels 8 | Power supply type DC voltage Power consumption (typical) | DC 12 V 17 W |
| HDMI ports quantity VGA (D-Sub) output ports | 1 1 | Weight & dimensions | |
| Audio input | 1 | Width | 260 mm |
| Audio output | 1 | Depth | 222 mm |
| USB 2.0 ports quantity | 2 | Height | 45 mm |
| Network | | Weight | 1.1 kg |
| Ethernet LAN | / | Operational conditions | |
| Ethernet interface type | Fast Ethernet | Operating temperature (T-T) Operating relative humidity (H-H) | -10 - 55 °C 10 - 90% |

