



Canon imageFORMULA R40 ADF + Escáner de alimentación de hojas 600 x 600 DPI A4 Negro, Blanco

Marca : Canon

Familia de productos:
imageFORMULA

Código del producto:
4229C001

Nombre del producto : R40



CMOS CIS, LED RGB, 600 dpi, 40 ppm/80 ipm, ADF, USB 2.0, 291 x 250 x 245 mm, 2.8 kg

Canon imageFORMULA R40 ADF + Escáner de alimentación de hojas 600 x 600 DPI A4 Negro, Blanco:

ESCÁNER PARA GRUPOS DE TRABAJO

Facilita y comparte información instantáneamente utilizando servicios online como cuentas de correo o en la nube en un solo paso.

DISEÑO

Diseñado para espacios de trabajo reducidos en casa y oficinas. Configuración e inicio rápido de escaneo solo presionando un botón. Alimentador con capacidad de 60 hojas para facilitar el escaneo.

Scanning		Paper handling	
Maximum scan size *	216 x 356 mm	Auto Document Feeder (ADF) media weight	20 - 209 g/m ²
Optical scanning resolution *	600 x 600 DPI	Maximum scan width	21.6 cm
Colour scanning	✓	Maximum scan length	3 m
Duplex scanning *	✓	Maximum scan area (ADF)	216 x 356 mm
Output colour depth	24 bit	Minimum scan area (ADF)	50.8 x 54 mm
Greyscale levels	256	Ports & interfaces	
ADF scan speed (b/w, A4)	40 ppm	USB port *	✓
ADF scan speed (colour, A4)	30 ppm	USB version	2.0
Design		Power	
Scanner type *	ADF + Sheet-fed scanner	Power supply type *	AC
Product colour *	Black, White	Power consumption (typical)	22 W
Display	LED	Power consumption (off)	0.1 W
Built-in display *	✗	AC input frequency	50 - 60 Hz
Performance		Input voltage	100 - 240 V
Sensor type *	CMOS CIS	Power consumption (sleep)	1.4 W
Light source	RGB LED	Weight & dimensions	
Daily duty cycle (max) *	4000 pages	Width	250 mm
Scan drivers	TWAIN	Depth	291 mm
Input capacity		Height	245 mm
Auto document feeder (ADF) input capacity	60 sheets	Weight	2.8 kg
Paper handling		Packaging data	
Long-paper mode	✓	Quantity per pack	1 pc(s)
Maximum ISO A-series paper size *	A4	System requirements	
Legal	✓	Windows operating systems supported	Windows 10, Windows 10 x64, Windows 8.1, Windows 8.1 x64, Windows XP
Media thickness (min)	0.04 mm	Mac operating systems supported	Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina
Card thickness (max)	1.4 mm	Logistics data	
		Harmonized System (HS) code	84716070

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date