

## Dahua Technology WizMind DH-IPC-HFW5449T-ASE-LED cámara de vigilancia Bala (forma) Cámara de seguridad IP Interior y exterior 2688 x 1520 Pixeles Techo/pared

Marca: Dahua Technology

Familia de productos: WizMind

Código del producto: DH-IPC-HFW5449T-ASE-LED

Nombre del producto: DH-

IPC-HFW5449T-ASE-LED

Dahua Technology WizMind DH-IPC-HFW5449T-ASE-LED. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared, Color del producto: Blanco, Factor de forma: Bala (forma). Ángulo de rotación: 360°, Ángulo de inclinación: 0 - 90°, Rango de paneo: 0 - 360°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 1.8 mm (1 / 1.8"), Número de píxeles efectivos (A x V): 2688 x 1520 Pixeles. Iluminación mínima (cámara panorámica): 0.0005 Lux, Relación señal/ruido (SNR) (cámara panorámica): 56 Db





Performance		Audio	
Type *	IP security camera	Audio input channels	1 channels
Placement supported *	Indoor & outdoor	Audio output channels	1 channels
Connectivity technology *	Wired	Network	
People counting function	•	Ethernet LAN *	<b>✓</b>
Wide Dynamic Range (WDR)	•	Ethernet interface type	Fast Ethernet
Day/night mode	✓	Networking standards	IEEE 802.1x
Design Form factor * Mounting type * Product colour *	Bullet Ceiling/wall White	Supported network protocols	IPv4; IPv6; HTTP; HTTPS; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; 802.1x; SNMP
LED indicators	<b>√</b>	Wi-Fi *	×
Housing material	Metal	Bluetooth *	×
International Protection (IP) code	IP67	Number of users	20 user(s)
Weatherproof	✓	Storage	
Fog proof	✓	Compatible memory cards	MicroSD (TransFlash)
Camera		Internal memory	512 MB
Angle of rotation	360°	ROM capacity	128 MB
Tilt angle range	0 - 90°	Ports & interfaces	
Pan range	0 - 360°	Ethernet LAN (RJ-45) ports	1
Image sensor		Security	
Number of sensors	1	Alarm input channels	1
Optical sensor size	25.4 / 1.8 mm (1 / 1.8")	Alarm output channels	1
Progressive scan Sensor type *	CMOS	Intelligent Video Surveillance (IVS) system features	Abandoned object, Face detection, Intrusion, Missing object, People counting, Tripwire
Number of effective pixels (H x V)	2688 x 1520 pixels	Mirror	<b>/</b>
		Digital watermark	/

Panoramic camera		Management features	
Minimum illumination (panoramic camera)	0.0005 lx	Web-based management	✓
Signal-to-Noise Ratio (SNR) (panoramic camera)	56 dB	Management software  Power	Smart PSS; DSS; DMSS
Lens system		Power source type *	DC, PoE
Number of lenses * Focal length range Maximum aperture number	1 2.8 - 6 mm 1	Power consumption (typical) Power consumption (max) Power consumption (Power over Ethernet (PoE))	2.6 W 7.3 W 8.5 W
Night vision		Operational conditions	
Night vision *	✓	Operating temperature (T-T)	-40 - 60 °C
Video		Storage temperature (T-T)	-40 - 60 °C
Maximum resolution *	2688 x 1520 pixels 4 MP H.264, H.264+, H.264B, H.264H, H.265, H.265+, M-JPEG 60 fps	Operating relative humidity (H-H)	0 - 95%
Total megapixels *		Weight & dimensions	
Video compression formats		Width	79 mm 244.1 mm
Frame rate		Depth Height	75.9 mm
Video streaming		Weight	815 g
		Packaging data	
		Package weight	1.08 kg
		Packaging content	
		Number of cameras *	1

