



Dahua Technology DH-IPC-HFW1239S1-A-LED-S5 cámara de vigilancia Bala (forma) Cámara de seguridad IP Interior y exterior 1920 x 1080 Pixeles Techo/pared/Tubo

Marca : Dahua Technology

Código del producto: DH-IPC-HFW1239S1-A-LED-S5

Nombre del producto : DH-IPC-HFW1239S1-A-LED-S5

Dahua Technology DH-IPC-HFW1239S1-A-LED-S5. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared/Tubo, Color del producto: Blanco, Factor de forma: Bala (forma). Iluminación mínima: 0.005 Lux, Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 107°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.8 mm (1 / 2.8"), Número de píxeles efectivos (A x V): 1920 x 1080 Pixeles. Distancia de detección: 43.9 m, Distancia de observación: 17.5 m, Distancia de reconocimiento: 8.8 m

Performance		Video	
Type *	IP security camera	Bit rate	H.264: 32 kbps-6144 kbps H.265: 12 kbps-6144 kbps
Placement supported *	Indoor & outdoor	Back Light Compensation (BLC)	✓
Connectivity technology *	Wired	Highlight Compensation (HLC)	✓
Wide Dynamic Range (WDR)	✓	Digital Wide Dynamic Range (DWDR)	✓
Day/night mode	✓	Region of Interest (ROI) encoding	✓
Built-in light	✓	Smart IR	✓
Certification	CE-LVD: EN 62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B	Audio	
Design		Signal-to-Noise Ratio (SNR)	56 dB
Form factor *	Bullet	Built-in microphone	✓
Mounting type *	Ceiling/Wall/Pole	Voice codecs	G.711Mu, G.711a, G.726
Product colour *	White	Bit rate range	32 - 6144 Kbit/s
Housing material	Metal, Plastic	Network	
International Protection (IP) code	IP67	Ethernet LAN *	✓
Camera		Ethernet interface type	Fast Ethernet
Minimum illumination	0.005 lx	Networking standards	IEEE 802.3af
Angle of rotation	360°	Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP
Lens viewing angle, horizontal	107°	Wi-Fi *	✗
Lens viewing angle, vertical	56°	Bluetooth *	✗
Lens viewing angle, diagonal	127°	Number of users	6 user(s)
Tilt angle range	0 - 90°	Client interoperability	ONVIF (Profile S); CGI; P2P; Genetec
Pan range	0 - 360°	Storage	
White balance	Auto, Manual, Natural, Outdoor, Regional custom, Street lamp	Built-in HDD *	✗
Camera shutter type	Electronic	Internal memory	64 MB
Camera shutter speed	1/3 - 1/100000 s	ROM capacity	16 MB
Adjustment shutter speed	Auto/Manual	Ports & interfaces	
Number of Privacy masking areas	4	Ethernet LAN (RJ-45) ports	1
Image sensor		Security	
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")	Video motion detection	✓
Progressive scan	✓	Security algorithms	WPA-SDK
Sensor type *	CMOS	Mirror	✓
Number of effective pixels (H x V)	1920 x 1080 pixels	Management features	
Lens system		Web-based management	✓
Detect distance	43.9 m		
Observe distance	17.5 m		
Recognize distance	8.8 m		

Lens system		Management features	
Maximum aperture number	1.6	Management software	Smart PSS; DSS; DMSS
Identify distance	4.4 m	Power	
Fixed focal length	2.8 mm	Power source type *	DC, PoE
Closest focusing distance	0.7 m	Power consumption (typical)	1.2 W
Night vision		Power consumption (max)	4.2 W
Night vision *	✓	Power consumption (Power over Ethernet (PoE))	5.4 W
Night vision distance	15 m	DC output voltage	12
Number of illumination LEDs	1	Operational conditions	
Video		Operating temperature (T-T)	-40 - 60 °C
Maximum resolution *	1920 x 1080 pixels	Storage temperature (T-T)	-40 - 60 °C
Total megapixels *	2 MP	Operating relative humidity (H-H)	0 - 95%
Video compression formats	H.264, H.264+, H.264B, H.264H, H.265, H.265+	System requirements	
Supported graphics resolutions	1280 x 960, 352 x 288, 352 x 240, 640 x 480 (VGA), 1920 x 1080 (HD 1080), 1280 x 720 (HD 720), 704 x 576, 704 x 480	Mobile operating systems supported	Android, iOS
Supported video modes	720p, 1080p	Weight & dimensions	
Frame rate	30 fps	Width	70 mm
Video streaming	✓	Depth	162.6 mm
Noise reduction	✓	Height	70 mm
Noise reduction technology	3D noise reduction	Weight	220 g
Gain control type	Auto/Manual	Packaging data	
Privacy masking	✓	Package weight	340 g
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)	Packaging content	
		Number of cameras *	1
		Other features	
		Browser supported	IE; Chrome; Firefox
		Technical details	
		Number of video streams	2

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date