



Dahua Technology IPC DH- -HDW1239T1-A-LED-S5 cámara de vigilancia Domo Cámara de seguridad IP Interior y exterior 1920 x 1080 Píxeles Techo

Marca : Dahua Technology

Familia de productos: IPC

Código del producto: DH-IPC-HDW1239T1-A-LED-S5

Nombre del producto : DH-IPC-HDW1239T1-A-LED-S5



Dahua Technology IPC DH- -HDW1239T1-A-LED-S5. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo, Color del producto: Blanco, Factor de forma: Domo. Iluminación mínima: 0.005 Lux, Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 107°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.8 mm (1 / 2.8"), Número de píxeles efectivos (A x V): 1920 x 1080 Píxeles. Distancia de detección: 43.9 m, Distancia de observación: 17.5 m, Distancia de reconocimiento: 8.8 m

Performance		Video	
Type *	IP security camera	Privacy masking	✓
Placement supported *	Indoor & outdoor	Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Connectivity technology *	Wired	Bit rate	H.264: 32 kbps-6144 kbps H.265: 12 kbps-6144 kbps
Wide Dynamic Range (WDR)	✓	Back Light Compensation (BLC)	✓
Day/night mode	✓	Highlight Compensation (HLC)	✓
Built-in light	✓	Digital Wide Dynamic Range (DWDR)	✓
Certification	CE-LVD: EN 62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B	Region of Interest (ROI) encoding	✓
Design		Smart IR	✓
Form factor *	Dome	Audio	
Mounting type *	Ceiling	Signal-to-Noise Ratio (SNR)	56 dB
Product colour *	White	Built-in microphone	✓
Housing material	Metal, Plastic	Voice codecs	G.711Mu, G.711a, G.726
International Protection (IP) code	IP67	Bit rate range	12 - 6144 Kbit/s
Weatherproof	✓	Network	
Camera		Ethernet LAN *	✓
Minimum illumination	0.005 lx	Ethernet interface type	Fast Ethernet
Angle of rotation	360°	Networking standards	IEEE 802.3af
Lens viewing angle, horizontal	107°	Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP
Lens viewing angle, vertical	56°	Wi-Fi *	✗
Lens viewing angle, diagonal	127°	Bluetooth *	✗
Tilt angle range	0 - 78°	Number of users	6 user(s)
Pan range	0 - 360°	Client interoperability	ONVIF (Profile S); CGI; P2P; Genetec
White balance	Auto, Manual, Natural, Outdoor, Regional custom, Street lamp	Storage	
Camera shutter type	Electronic	Built-in HDD *	✗
Camera shutter speed	1/3 - 1/100000 s	Internal memory	64 MB
Adjustment shutter speed	Auto/Manual	ROM capacity	16 MB
Number of Privacy masking areas	4	Ports & interfaces	
Image sensor		Ethernet LAN (RJ-45) ports	1
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")		
Progressive scan	✓		
Sensor type *	CMOS		
Number of effective pixels (H x V)	1920 x 1080 pixels		

Panoramic camera		Security	
Digital Wide Dynamic Range (DWDR) (panoramic camera)	✓	Video motion detection	✓
Lens system		Active tampering alarm	✓
Detect distance	43.9 m	Mirror	✓
Observe distance	17.5 m	Digital watermark	✓
Recognize distance	8.8 m	Management features	
Maximum aperture number	1.6	Management software	Smart PSS; DSS; DMSS
Identify distance	4.4 m	Power	
Fixed focal length	2.8 mm	Power source type *	DC, PoE
Closest focusing distance	0.7 m	Power consumption (typical)	1.2 W
Night vision		Power consumption (max)	5.4 W
Night vision *	✓	Power consumption (Power over Ethernet (PoE))	2 W
Night vision distance	15 m	DC output voltage	12
Number of illumination LEDs	1	Operational conditions	
Video		Operating temperature (T-T)	-40 - 60 °C
Maximum resolution *	1920 x 1080 pixels	Storage temperature (T-T)	-40 - 60 °C
Total megapixels *	2 MP	Operating relative humidity (H-H)	0 - 95%
Video compression formats	H.264, H.264+, H.264B, H.264H, H.265, H.265+	System requirements	
Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)	Mobile operating systems supported	Android, iOS
Frame rate	30 fps	Weight & dimensions	
Video streaming	✓	Height	85.5 mm
Noise reduction	✓	Diameter	10.9 cm
Noise reduction technology	3D noise reduction	Weight	240 g
Gain control type	Auto/Manual	Packaging data	
		Package weight	370 g
		Packaging content	
		Number of cameras *	1
		Other features	
		Browser supported	IE; Chrome; Firefox
		Technical details	
		Number of video streams	2

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date