



Dahua Technology DHI-ISC-D718-TNS2 detector de metales para seguridad

Marca : Dahua Technology

Código del producto: DHI-ISC-D718-TNS2

Nombre del producto : DHI-ISC-D718-TNS2

Dahua Technology DHI-ISC-D718-TNS2. Tipo de producto: Walk through. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.7 mm (1 / 2.7"), Total de megapíxeles: 4 MP. Tipo de sensor (módulo térmico): Vanadium Oxide Uncooled Focal Plane Arrays, Resolución del sensor (módulo térmico): 256 x 192 Píxeles, Paso de pixel (módulo térmico): 12 µm. Tarjetas de memoria compatibles: MicroSD (TransFlash), Protocolos de red compatibles: HTTPS; HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; SNMP;..., Certificación: GB15210-2018 IEC 60068-2-1 IEC 60068-2-2 CE-LVD: EN62368-1 CE-EMC: Electromagnetic Compatibility.... Fuente de energía: CA/CD, Voltaje de entrada AC: 100 - 240 V, Voltaje de entrada DC: 12 V



Design		Thermal module	
Product type *	Walk through	Vertical field of view (thermal module)	37.8°
Camera		Detect distance (human)	146 m
Sensor type	CMOS	Detect distance (vehicle)	389 m
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	Recognize distance (human)	38 m
Total megapixels	4 MP	Recognize distance (vehicle)	97 m
Maximum resolution	2336 x 1752 pixels	Identify distance (human)	19 m
Camera shutter speed	1/30000 s	Identify distance (vehicle)	49 m
Minimum illumination	0.05 lx	Features	
Fixed focal length	4 mm	Audible alarm(s)	✓
Day/night mode	✓	Infrared (IR) sensor	✓
Infrared (IR) cut-off filter	✓	Card reader integrated	✓
Back Light Compensation (BLC)	✓	Compatible memory cards	MicroSD (TransFlash)
Highlight Compensation (HLC)	✓	Supported network protocols	HTTPS; HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; SNMP; QoS; UPnP; NTP
Digital Wide Dynamic Range (DWDR)	✓	Certification	GB15210-2018 IEC 60068-2-1 IEC 60068-2-2 CE-LVD: EN62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B
Thermal module		Ports & interfaces	
Sensor type (thermal module)	Vanadium Oxide Uncooled Focal Plane Arrays	Ethernet LAN (RJ-45) ports	1
Sensor resolution (thermal module)	256 x 192 pixels	RS-485 ports	1
Pixel pitch (thermal module)	12 µm	Power	
Spectrum range (thermal module)	8 - 14 µm	Power source	AC/DC
Thermal sensitivity (NETD)	50 mK	AC input voltage	100 - 240 V
Fixed focal length (thermal module)	3.5 mm	DC input voltage	12 V
Aperture number (thermal module)	1		
Digital zoom	16x		
Horizontal field of view (thermal module)	50.6°		

Power	
Power consumption (typical)	23 W
Power consumption (standby)	10 W
Weight & dimensions	
Width	927.8 mm
Depth	571.8 mm
Height	2210 mm

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date