## Buffalo TeraStation TS51220RH6404 servidor NAS o de almacenamiento Bastidor (2U) Annapurna Labs AL524 16 GB DDR4 64 TB Unidad de disco duro Negro

Familia de productos: Código del producto: TeraStation TS51220RH6404

## Nombre del producto:

TS51220RH6404

Marca: Buffalo

16TBx4, RAID 0/1/5/6/10/JBOD, 2x USB 3.2; 2x USB 2.0, RJ-45 Buffalo TeraStation TS51220RH6404. Tipo: NAS. Tipo de chasis: Bastidor (2U). Clase del dispositivo: Grandes empresas. Familia de procesador: Annapurna Labs, Modelo del procesador: AL524, Frecuencia del procesador: 2.04 GHz. Memoria interna: 16 GB, Tipo de memoria interna: DDR4. Capacidad de almacenamiento total instalado: 64 TB, Tipo de unidades de almacenamiento instaladas: Unidad de disco duro



Storage		Ports & interfaces	
Storage drive capacity *	240 TB	Ethernet LAN (RJ-45) ports *	4
Storage drive interface *	Serial ATA III	Design	
	0, 1, 5, 6, 10, JBOD	Chassis type * Product colour	Rack (2U) Black
Storage drives installed *	✓ (4.75)	Performance	
Number of storage drives installed * Number of storage drives supported *	12	Type * Device class *	NAS Large Enterprise Business
		Software	
Installed storage drive type *  Processor	HDD	Windows operating systems supported	Windows 10, Windows 11, Windows 8.1
Processor manufacturer *	Annapurna Labs	Mac operating systems supported	Mac OS X 10.13 High Sierra
Processor model *	Annapurna Labs AL524	Server operating systems supported	Windows Server 2019, Windows Server 2022
Processor frequency *	2.04 GHz	Power	
Processor cores	4	AC input voltage	100 - 240 V
Memory		AC input frequency	50 - 60 Hz
Internal memory *	16 GB	Weight & dimensions	
Internal memory type	DDR4	Width *	480 mm
Network		Depth *	736.6 mm
Ethernet LAN *	<b>✓</b>	Height * Weight	86.4 mm 25.1 kg
Ethernet LAN data rates	10,100,1000,10000 Mbit/s	Package width	581.7 mm
Ports & interfaces		Package depth	977.9 mm
USB port *	<b>✓</b>	Package height	259.1 mm
USB 2.0 ports quantity	2	Package weight	30.2 kg
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2	Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 10 - 85%





747464135397

0747464135397

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.