

Buffalo TeraStation TS5420RN NAS Bastidor (1U) Annapurna Labs 8 GB DDR4 16 TB Unidad de disco duro Negro

Marca : Buffalo

Familia de productos:
TeraStation

Código del producto:
TS5420RN3204

Nombre del producto :
TS5420RN



Buffalo TeraStation TS5420RN. Tipo: NAS. Tipo de chasis: Bastidor (1U). Familia de procesador: Annapurna Labs, Frecuencia del procesador: 2.04 GHz. Memoria interna: 8 GB, Tipo de memoria interna: DDR4. Capacidad de almacenamiento total instalado: 16 TB, Tipo de unidades de almacenamiento instaladas: Unidad de disco duro



Storage		Ports & interfaces	
Storage drive capacity *	8 GB	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
RAID support *	✓	Ethernet LAN (RJ-45) ports *	3
RAID levels	0, 1, 5, 6, 10, JBOD	Design	
Hot-swap drive bays	✓	Chassis type *	Rack (1U)
Storage drives installed *	✓	Cooling type *	Active
Total installed storage capacity *	16 TB	Product colour	Black
Number of storage drives installed *	4	Performance	
Number of storage drives supported *	4	Type *	NAS
Installed storage drive type *	HDD	Backup function *	✓
Supported storage drive types *	HDD	Backup features	iSCSI LUN
Processor		Snapshot	✓
Processor manufacturer *	Annapurna Labs	Software	
Processor family *	Annapurna Labs	Windows operating systems supported	✓
Processor frequency *	2.04 GHz	Mac operating systems supported	✓
Processor cores	4	Power	
Memory		Power consumption (max)	100 W
Internal memory *	8 GB	AC input voltage	100 - 240 V
Internal memory type	DDR4	AC input frequency	50 - 60 Hz
Network		Weight & dimensions	
Ethernet LAN *	✓	Width *	430 mm
Ethernet LAN data rates	1000,10000 Mbit/s	Depth *	430 mm
Ethernet LAN data rate supported (max)	10000 Mbit/s	Height *	44.2 mm
iSCSI support	✓	Weight	8.48 kg
Supported network protocols	TCP/IP	Package width	309.9 mm
Data link protocols	CIFS/SMB, AFP, FTP/FTPS/SFTP, NFS	Package depth	358.1 mm

Ports & interfaces		Weight & dimensions	
USB port *	✓	Package height	363.2 mm
USB 2.0 ports quantity	2	Package weight	12.3 kg
Operational conditions			
		Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	10 - 85%



0747464135939



747464135939

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date