## Huawei S2700-18TP-EI-AC dispositivo de redes Gestionado

Marca : Huawei Código del producto: S2700-18TP-EI-AC

Nombre del producto: S2700-18TP-EI-AC



Huawei S2700-18TP-EI-AC. Tipo de interruptor: Gestionado. Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 16, Número de módulos SFP instalados: 2, Puerto de consola: RJ-45. Tabla de direcciones MAC: 8000 entradas. Estándares de red: IEEE 802.1Q, IEEE 802.1p. Conector eléctrico: Toma de entrada de CC. Montaje en rack

Management features		Multicast features	
Switch type *	Managed	Multicast support	✓
Quality of Service (QoS) support	✓	Protocols	
Ports & interfaces		Supported network protocols	SNMP V1/V2/V3, RMON, HGMP v2,
Basic switching RJ-45 Ethernet ports quantity *	16	Design	SSHv2, GVRP
Fast Ethernet (copper) ports quantity	16	Rack mounting *	<b>✓</b>
Gigabit Ethernet (copper) ports quantity	2	Stackable *	✓
Installed SFP modules quantity *	2	Power	
Console port	RJ-45	Power source *	AC
Power connector	DC-in jack	Power supply included *	<b>✓</b>
Network		AC input voltage	100 - 220 V
Networking standards *	IEEE 802.1Q, IEEE 802.1p	AC input frequency	50 - 60 Hz
10G support *	×	Power consumption (typical)	12.8 W
Flow control support	<b>√</b>	Power over Ethernet (PoE)	
Rate limiting	<b>✓</b>	Power over Ethernet (PoE) *	×
VLAN support	✓	Operational conditions	
Number of VLANs	4000	Operating temperature (T-T)	0 - 50 °C
Data transmission		Storage temperature (T-T)	-5 - 55 °C
MAC address table *	8000 entries	Operating relative humidity (H-H)	10 - 90%
Security		Weight & dimensions	
IGMP snooping	•	Width Depth Height Weight	442 mm 220 mm 43.6 mm 2.4 kg

