Huawei S2700-9TP-SI-AC Gestionado L2/L3 Fast Ethernet (10/100) Negro, Gris



Marca : Huawei Código del producto: 02352337

Nombre del producto: S2700-9TP-SI-AC



S2700-9TP-SI-AC Mainframe(8 FE RJ45, 1 GE Combo, AC 110/220V)
Huawei S2700-9TP-SI-AC. Tipo de interruptor: Gestionado, Capa del interruptor: L2/L3. Puertos tipo básico de conmutación RJ-45 Ethernet: Fast Ethernet (10/100), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 8, Número de módulos SFP instalados: 1, Puerto de consola: RJ-45. Tabla de direcciones MAC: 8000 entradas, Capacidad de conmutación: 32 Gbit/s. Estándares de red: IEEE 802.1D, IEEE 802.1p, IEEE 802.1p, IEEE 802.1v, IEEE 802.1x

Management features		Security	
Switch type * Switch layer Quality of Service (QoS) support	Managed L2/L3 ✓	Authentication type CPU defense Queue scheduling algorithms MAC address entries	AAA, RADIUS SP, WRR+SP Blackhole MAC address entries
Web-based management Traffic classification	√	Multicast features	Diackitole MAC address entities
iStack technology	·	Multicast support	✓
Ports & interfaces		Huicicust support	Interface-based multicast traffic
Basic switching RJ-45 Ethernet ports quantity *	8	Multicast features	statistics, Multicast traffic suppression
Basic switching RJ-45 Ethernet ports	Fast Ethernet (10/100)	Protocols	
type * Fast Ethernet (copper) ports	8	Management protocols	CLI, SNMP v1/v2c/v3, SSHv2, IGMPv1,IGMPv2,IGMPv3
quantity Installed SFP modules quantity *	1	Supported network protocols	SNMP V1/V2/V3, RMON, HGMP v2, SSHv2, GVRP
Console port	RJ-45	Multicast protocols	IGMP v1/v2/v3
Network		Design	
Networking standards * 10G support *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x	Stackable * Product colour LED indicators	✔ Black, Grey ✔
Flow control support	` '	Performance	
Link aggregation	✓	Sleep mode	✓
Rate limiting	✓	Telnet	✓
VLAN support	✓	Power	
Virtual LAN features	VLAN Identifier (VLAN ID), Portbased VLAN	Power supply included *	v 1
Number of VLANs	4000	Number of power supply units AC input voltage	90 - 264 V
Data transmission Switching capacity *	32 Gbit/s	AC input frequency Power consumption (typical)	50 - 60 Hz 12.8 W
Throughput	2.7 Mpps	Power over Ethernet (PoE)	
MAC address table * Number of queues	8000 entries 8	Power over Ethernet (PoE) *	×
Static route	✓	Other features	
Security		Connectivity technology	Wired
DHCP features	DHCP snooping	Operational conditions	
IGMP snooping	✓	Operating temperature (T-T)	0 - 50 °C
Security algorithms	802.1x RADIUS, SNMP, SNMPv3, SSH-2	Storage temperature (T-T) Operating relative humidity (H-H)	-5 - 55 °C 10 - 90%
SSH/SSL support	✓	Weight & dimensions	
DoS attack prevention	✓	Width	250 mm
ARP attack prevention	✓	Depth	180 mm

Weight & dimensions		
Height	43.6 mm	
Weight	1.4 kg	
Packaging content		
Cables included	AC	

