## Imou Cruiser SE+ Domo Cámara de seguridad IP Exterior 2560 x 1440 Pixeles Techo/pared

Marca : Imou Código del producto: IPC-S41FEP-IMOU

Nombre del producto: Cruiser SE+

Imou Cruiser SE+. Tipo: Cámara de seguridad IP, Colocación compatible: Exterior, Tecnología de conectividad: Inalámbrico y alámbrico. Tipo de montaje: Techo/pared, Color del producto: Blanco, Factor de forma: Domo. Ángulo de visión del objetivo, horizontal: 79°, Ángulo de visión del objetivo, vertical: 44°, Ángulo de visión de la lente, diagonal: 94°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 3 mm (1 / 3"). Zoom digital: 16x, Diámetro de lente: 3.6 mm

| Performance   |  | Network   |  |
|---|--|---|--|
| Type * Placement supported * Connectivity technology * Antenna type | IP security camera Outdoor Wired & Wireless External 2 | Supported network protocols Wi-Fi * Wi-Fi standards Bluetooth * | ONVIF<br><b>v</b><br>802.11g, 802.11b, Wi-Fi 4 (802.11n)<br><b>x</b> |
| Antennas quantity Certification                                     | FCC  | Storage   |  |
| Design  |  | Built-in HDD *  | ×  |
| Form factor * Mounting type *                                       | Dome<br>Ceiling/wall                                   | Compatible memory cards  Maximum memory card size               | MicroSD (TransFlash)<br>256 GB                                       |
| Product colour *  | White  | Ports & interfaces  |  |
| Housing material  | Plastic  | Ethernet LAN (RJ-45) ports                                      | 1  |
| Protection features   | Dust resistant, Waterproof                             | Security  |  |
| International Protection (IP) code Weatherproof                     | IP66<br>✓  | Siren noise level   | 110 dB   |
|   | •  | Video motion detection  | ✓  |
| Camera  |  | Alert notification type   | Text alert message   |
| Camera pan control  Camera tilt control                             | <b>/</b>   | Intelligent Video Surveillance (IVS) system features            | Human detection  |
| Lens viewing angle, horizontal                                      | 79°  | Configurable region   | <b>✓</b>   |
| Lens viewing angle, vertical  | 44°  | Management features   |  |
| Lens viewing angle, diagonal  | 94°  | Reset button  | ✓  |
| Tilt angle range  | 0 - 90°  | Power   |  |
| Pan range   | 0 - 355°   | Power source type *   | DC   |
| Image sensor  |  | Power consumption (typical)                                     | 6.2 W  |
| Optical sensor size   | 25.4 / 3 mm (1 / 3")                                   | DC output voltage   | 12   |
| Progressive scan Sensor type *                                      | ✓ CMOS   | DC output current   | 1 A  |
|   | CMO3   | Operational conditions  |  |
| Lens system   | ,  | Operating temperature (T-T)                                     | -20 - 50 °C  |
| Zoom capability  Digital zoom                                       | <b>✓</b><br>16x  | Operating relative humidity (H-H)                               | 0 - 95%  |
| Number of lenses *  | 1  | System requirements   | LA. duid 100   |
| Lens diameter   | 3.6 mm   | Mobile operating systems supported                              | Android, IOS   |
| Night vision  |  | Weight & dimensions   |  |
| Night vision *  | ✓  | Width<br>Depth  | 120.7 mm<br>136.2 mm   |
| Night vision distance   | 30 m   | Height  | 183.3 mm   |
| Video   |  | Weight  | 395 g  |
| Maximum resolution *  | 2560 x 1440 pixels                                     | Sustainability  |  |
| Total megapixels *  | 4 MP   | Sustainability compliance                                       | 1  |
| Video compression formats   | H.265  | Compliance certificates   | UKCA, CE   |
| Frame rate  | 25 fps   | Packaging content   |  |
|   |  | Number of cameras *   | 1  |
|   |  |   |  |

| Audio                   |               | Packaging content          |   |
|-------------------------|---------------|----------------------------|---|
| Built-in speaker(s)     | ✓             | Mounting brackets included | ✓ |
| Audio system            | 2-way         | Screws included            | ✓ |
| Built-in microphone     | ✓             | Manual                     | ✓ |
| Network                 |               | AC adapter included        | ✓ |
| Ethernet LAN *          | <b>✓</b>      | Anchors included           | ✓ |
| Ethernet interface type | Fast Ethernet | Mounting template          | ✓ |
|                         |               | Waterproof connector       | ✓ |



6971927236886

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.