## Epson TM-T88VII-012 180 x 180 DPI Alámbrico Térmico Impresora de TPV

Marca: Epson Código del producto: C31CJ57012

Nombre del producto: TM-T88VII (112A0): USB,

Ethernet, Serial, PS, UK, Black

Epson TM-T88VII-012. Tecnología de impresión: Térmico, Tipo: Impresora de TPV, Resolución máxima: 180 x 180 DPI. Grosor de la impresión: 48 - 80 µm, Máximo diámetro del rollo: 8.3 cm, Ancho de papel soportado: 80 mm. Tecnología de conectividad: Alámbrico, Conector USB: USB Type-A / USB Type-B, Tipo de serie de interfaz: RS-232. Código de barras incorporado: CODABAR (NW-7), Code 128 (A/B/C), Code 39, Code 93, EAN13, EAN8, GS1 DataBar, GS1-128, ITF, UPC-A,..., Nivel de presión sonora (imprimiendo): 52 Db, Nivel de presión sonora (en espera): 52 Db. Color del producto: Negro





Printing		Design	
Print speed Character size Printing characters Character sets Print technology *	180 x 180 DPI 500 mm/sec 1.41 x 3.39 mm Text, Graphic, Barcode, 2D barcode ANK Thermal POS printer	Product colour *	Black
		Power	
		Power source type * Power consumption (printing) AC input voltage Power consumption Power consumption (standby)	DC 27.9 W 24 V 27900 mA 1400 mA
Paper handling		Power consumption (standby)	1.4 W
Printing media thickness Maximum roll diameter Supported paper width Media thickness	48 - 80 μm 8.3 cm 80 mm 48 - 80 mm	Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	5 - 45 °C 10 - 90% 10 - 90%
Ports & interfaces		System requirements	
USB port * ✓ USB connector USB *	USB Type-A / USB Type-B	Pre-installed software	Server Direct Print, ePOS-Device, ePOS-Display, ePOS-Print
Serial interface *		Weight & dimensions	
Serial interface type RS-232  Connectivity technology * Wired  Near Field Communication (NFC) ✓  Optional connectivity Wireless LAN	Wired 🗸	Width Depth Height Weight	145 mm 195 mm 148 mm 1.7 kg
Network		Packaging data	
Ethernet LAN * Wi-Fi *	×	Quantity per pack Package width Package depth Package height Package weight	1 pc(s) 195 mm 235 mm 260 mm 2.7 kg

Features		Print technology	
Built-in barcodes *	CODABAR (NW-7), Code 128 (A/B/C), Code 39, Code 93, EAN13, EAN8, GS1 DataBar, GS1-128, ITF, UPC-A, UPC-E 52 dB 52 dB 360000 h 3 million cuts  200 km Horizontal/Vertical	Column capacity	42/56
		Logistics data	
Sound pressure level (printing) Sound pressure level (standby) Mean time between failures (MTBF)		Pallet weight (UK) Products per pallet Pallet gross weight Products per pallet (UK)	0 g 112 pc(s) 0 g 168 pc(s)
Autocutter durability		Technical details	
Paper save function Print head life Mounting position		Changeable interface Lifetime	20000000 lines
Wall mountable	✓	Other features	
Built-in sensors details	Paper End Sensor, Paper Near End Sensor, Cover Open Sensor, Receipt paper sensor	Buffer size Mean cycles between failures (MCBF)	4 KB 70000000
Certification	CE		

