



Lenovo ThinkSystem SR630 V2 servidor Bastidor (1U) Intel® Xeon Silver 4314 2.4 GHz 32 GB DDR4-SDRAM 750 W



Marca : Lenovo

Familia de productos:
ThinkSystem

Código del producto:
7Z71A07SLA

Nombre del producto : SR630
V2

Lenovo ThinkSystem SR630 V2. Familia de procesador: Intel® Xeon Silver, Frecuencia del procesador: 2.4 GHz, Modelo del procesador: 4314. Memoria interna: 32 GB, Tipo de memoria interna: DDR4-SDRAM, Diseño de memoria (ranuras x tamaño): 1 x 32 GB. Ethernet. Fuente de alimentación: 750 W, Suministro de energía redundante (RPS), soporte. Tipo de chasis: Bastidor (1U)

Processor		Design	
Processor manufacturer *	Intel	Rack mounting	✓
Processor family *	Intel Xeon Silver	Redundant fans support	✓
Processor model *	4314	Performance	
Processor frequency *	2.4 GHz	Performance management	XClarity Enterprise
Processor boost frequency	3.4 GHz	Noise level	56 dB
Processor cache	24 MB	BIOS type	UEFI
Number of processors installed	1	Trusted Platform Module (TPM)	✓
Maximum number of SMP processors	2	Trusted Platform Module (TPM) version	2.0
Memory		Software	
Internal memory *	32 GB	Operating system installed *	✗
Internal memory type *	DDR4-SDRAM	Compatible operating systems *	
Memory slots	32x DIMM	Microsoft Windows Server 2016	
ECC	✓	Microsoft Windows Server 2019	
Memory clock speed	3200 MHz	Microsoft Windows Server 2022 Red Hat Enterprise Linux 7.9 Red Hat Enterprise Linux 8.2 Red Hat Enterprise Linux 8.3 SUSE Linux Enterprise Server 12 SP5 SUSE Linux Enterprise Server 12 Xen SP5 SUSE Linux Enterprise Server 15 SP2 SUSE Linux Enterprise Server 15 Xen SP2 VMware ESXi 6.7 U3 VMware ESXi 7.0 U2	
Memory layout (slots x size)	1 x 32 GB		
Storage		Power	
RAID support *	✓	Redundant power supply (RPS) support *	✓
Supported RAID controllers	940-8i 4GB	Power supply *	750 W
Optical drive type *	✗	Number of redundant power supplies supported	2
Internal drive bays	8	Number of redundant power supplies installed	1
Graphics		Operational conditions	
Maximum graphics card memory	16 MB	Storage temperature (T-T)	-40 - 60 °C
Network		Storage relative humidity (H-H)	8 - 90%
Wake-on-LAN ready	✓	Weight & dimensions	
Ethernet LAN	✓	Width	440 mm
Ports & interfaces		Depth	773 mm
USB 2.0 ports quantity	1	Height	43 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4		
VGA (D-Sub) ports quantity	2		
Design			
Chassis type *	Rack (1U)		
Product colour	Black		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date