
## Samsung QB24R-B Pantalla plana de señalización digital 61 cm (24") Wifi 250 cd / $m^2$ Full HD Negro Procesador incorporado Tizen 4.0

Marca : Samsung Código del producto: LH24QBRBBGCXZA

Nombre del producto: QB24R-B







Display		Design	
Panel type Display diagonal * Display resolution *	ADS 61 cm (24") 1920 x 1080 pixels	Bezel width (bottom) Bezel width (side) Bezel width (top)	1.79 cm 9.4 mm 1.79 cm
Display brightness * HD type * Touchscreen * Native aspect ratio Response time Contrast ratio (typical) Contrast ratio (dynamic) Viewing angle, horizontal Viewing angle, vertical Display number of colours Pixel pitch	250 cd/m <sup>2</sup> Full HD  X 16:9 14 ms 1000:1 4000:1 178° 178° 16.7 million colours 0.2745 x 0.2745 mm	Performance Purpose * HDCP International Protection (IP) code HDCP version  Power  Power consumption (typical) * Power consumption (standby) * Power consumption (sleep) AC input voltage	Universal  ✓ IP5X 2.2  25 W 0.5 W 0.5 W 100 - 240 V
Colour saturation Horizontal scan range Vertical scan range Haze rate	72% 48 - 75 kHz 56 - 84.5 Hz 25%	AC input frequency  Computer system  Built-in processor *	50 - 60 Hz ✓
Ports & interfaces		Processor manufacturer Processor family	ARM ARM Cortex
HDMI ports quantity * HDMI input ports quantity DVI port * USB port * USB ports quantity	1 1 * *	Processor model Processor architecture Processor frequency Processor cores Operating system installed	A72 ARM Cortex-A72 1.7 GHz 4 Tizen 4.0
Ethernet LAN *	✓	Weight & dimensions	
Ethernet LAN (RJ-45) ports Wi-Fi * RS-232C Infrared data port	1 * * * * *	Width Depth Height Weight	547.9 mm 31.8 mm 334.4 mm 3 kg
Audio		Packaging data	
Built-in speaker(s) *	×	Package width	620 mm

Design		Packaging data	
Product design *	Digital signage flat panel	Package depth	122 mm
Placement supported *	Indoor	Package height	419 mm
Orientation	Horizontal/Vertical	Package weight	4.1 kg
Product colour *	Black  ✓ Operational conditions  Operating temperature (T-T)  100 x 100 mm Operating relative humidity	Operational conditions	
VESA mounting *		Operating temperature (T-T)	0 - 40 °C
Panel mounting interface		Operating relative humidity (H-H)	10 - 80%

