

## TP-Link JetStream TL-SG3452XP dispositivo de redes Gestionado L2+ Gigabit Ethernet (10/100/1000) Energía sobre Ethernet (PoE) 1U Negro

Código del producto: TL-Marca: TP-Link Familia de productos: JetStream

SG3452XP

Nombre del producto: TL-

SG3452XP

TP-Link JetStream TL-SG3452XP. Tipo de interruptor: Gestionado, Capa del interruptor: L2+. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 48, Puerto de consola: RJ-45/Micro-USB. Tabla de direcciones MAC: 16000 entradas, Capacidad de conmutación: 176 Gbit/s. Estándares de red: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3af, IEEE.... Conector eléctrico: Conector de entrada de CA. Energía sobre Ethernet (PoE). Montaje en rack, Factor de forma: 1U



Management features		Multicast features	
Switch type *	Managed	Multicast support	✓
Switch layer	L2+	Design	
Quality of Service (QoS) support	1	Rack mounting *	<b>✓</b>
Web-based management	1	Form factor	10
Cloud-managed	✓	Product colour	Black
ARP inspection	✓	Reset button	<b>✓</b>
Configuring Location Settings (CLI)	✓	LED indicators	<b>✓</b>
System event log	✓	Number of fans	3 fan(s)
Ports & interfaces		Power	
Basic switching RJ-45 Ethernet ports quantity *	48	Power source *	AC
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power supply included * AC input voltage	✓ 100 - 240 V
SFP+ module slots quantity	4	AC input frequency	50/60 Hz
Console port	RJ-45/Micro-USB	Power consumption (max)	635.7 W
Power connector	AC-in jack	Power over Ethernet (PoE)	
Network		Power over Ethernet (PoE) *	✓
	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab,	Power over Ethernet plus (PoE+) ports quantity	48
Networking standards *	IEEE 802.3ae, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3z	Power over Ethernet (PoE) power per port	30 W
10G support *	✓	Total Power over Ethernet (PoE) budget	500 W
Port mirroring	<b>✓</b>	Operational conditions	
Flow control support	✓	•	0 - 40 °C
Link aggregation	✓	Operating temperature (T-T) Storage temperature (T-T)	-40 - 70 °C
Broadcast storm control	/	Operating relative humidity (H-H)	10 - 90%
Rate limiting	1	Storage relative humidity (H-H)	5 - 90%

Network		Operational conditions	
Spanning tree protocol	✓	Heat dissipation	2169.2 BTU/h
Head-of-line (HOL) blocking	✓	Weight & dimensions	
VLAN support	✓	Width	440 mm
Data transmission		Depth	330 mm
Switching capacity *	176 Gbit/s	Height	44 mm
Forwarding rate	130.9 Mpps	Packaging content	
MAC address table *	16000 entries	Cables included	AC
Store-and-forward	<b>✓</b>	Quick start guide	✓
Jumbo frames support ✓		Packaging data	
Jumbo frames	9000	Package width	440 mm
Packet buffer memory	12 MB	Package depth	528 mm
Security		Package height	100 mm
DHCP features	DHCP client, DHCP relay, DHCP server	Package weight	6.48 kg
Access Control List (ACL)		Certificates	
IGMP snooping		Certification	CE, FCC, RoHS
MAC address filtering		Logistics data	
Static port security		Harmonized System (HS) code	85176990
SSH/SSL support	·		
BPDU filtering/protection	•		
IP-MAC-Port binding	•		
Authentication	Auto VLAN, Guest VLAN		
	,		





840030702518

0840030702518



6935364006501

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.