



APC NetShelter Rack PDU Advanced unidad de distribución de energía (PDUs) 40 salidas AC 0U Negro

Marca : APC

Código del producto: APDU10151ME

Nombre del producto : NetShelter Rack PDU Advanced



APC NetShelter Rack PDU Advanced. PDU tipos: Regulado, Capacidad del rack: 0U, Tipo: Monofásico. Cantidad de salidas AC: 40 salidas AC, Tipo de salida AC: Acoplador C13, Acoplador C15, Acoplador C19, Acoplador C21, Conector: NEMA L6-30P. Indicadores LED: Actividad, Red, Corriente, Longitud de cable: 3 m, Algoritmos de seguridad: 128-bit AES, 192-bit AES, 256-bit AES, DES, MD5, SNMP, SNMPv2, SNMPv3. Monitoreo: Corriente, Humedad, Corriente, Temperatura, Voltaje, Salida de control: Bloqueo, Reciclar, Apagar, Encender, Firmware actualizable a través de: Red, USB. Voltaje nominal de entrada: 200-240 V, Máxima corriente: 30 A, Frecuencia de entrada AC: 50 - 60 Hz

Design		Power	
PDU types *	Metered	AC input frequency	50 - 60 Hz
Type	Single-phase	Maximum current *	30 A
Form factor	Rackmount	Nominal output voltage	208 V
Rack capacity *	0U	Load capacity	4992 VA
Mounting	Vertical	Number of phases	1
Product colour	Black	Maximum total current draw per phase	24 A
Display	LCD	Power protection features	Overload
On/off switch	✓	Maximum power	5000 W
Regulatory Approvals	CSA C22.2 No 62368-1, FCC part 15 subpart B, UL 62368-1	Surge protection	✓
Ports & interfaces		Certificates	
AC outlets quantity *	40 AC outlet(s)	Compliance certificates	RoHS
Power plug	NEMA L6-30P	Operational conditions	
AC outlet types *	C13 coupler, C15 coupler, C19 coupler, C21 coupler	Operating temperature (T-T)	-5 - 60 °C
Ethernet LAN (RJ-45) ports	2	Storage temperature (T-T)	-25 - 65 °C
USB ports quantity	1	Operating relative humidity (H-H)	5 - 95%
Features		Storage relative humidity (H-H)	5 - 95%
Daisy chain	✓	Operating altitude	0 - 3048 m
Reset button	✓	Non-operating altitude	0 - 15240 m
LED indicators	Activity, Network, Power	Operating temperature (T-T)	23 - 140 °F
Colour-coded outlets	✓	Weight & dimensions	
Cable length	3 m	Width	56 mm
Security algorithms	128-bit AES, 192-bit AES, 256-bit AES, DES, MD5, SNMP, SNMPv2, SNMPv3	Depth	75 mm
Password protection	✓	Height	1490 mm
Compatible products	Compatible with most NetShelter SX enclosures and third-party racks	Weight	6.6 kg
		Packaging data	
		Package weight	8.6 kg

Management features		Packaging data	
Monitoring	Current, Humidity, Power, Temperature, Voltage	Package width	208 mm
Outlet control	Lock-out, Recycle, Turn off, Turn on	Package depth	116 mm
Firmware upgradeable	✓	Package height	1720 mm
Firmware upgradeable via	Network, USB		
Power			
Nominal input voltage *	200-240 V		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date