


GIGABYTE GP-UD750GM unidad de fuente de alimentación 750 W  
20+4 pin ATX ATX Negro

Marca : GIGABYTE

Código del producto: GP-UD750GM

Nombre del producto : GP-UD750GM



GIGABYTE GP-UD750GM. Potencia total: 750 W, Voltaje de entrada AC: 100 - 240 V, Frecuencia de entrada AC: 50 - 60 Hz. Alimentador de energía para tarjeta madre: 20+4 pin ATX, Longitud del cable de alimentación de la placa base: 61 cm, Longitud del cable de alimentación SATA: 150,300,450,600 mm. Utilizar con: PC, Factor de forma de fuente de alimentación (PSU): ATX, Certificación 80 PLUS: 80 PLUS Gold. Color del producto: Negro, Tipo de enfriamiento: Activo, Diámetro de ventilador: 12 cm. Cables incluidos: CPU, PCIe, Peripheral (Molex), SATA

Power		Ports & interfaces	
Total power *	750 W	PCI Express power cable length	60 cm
AC input voltage *	100 - 240 V	CPU power connector (4+4 pin)	✓
AC input frequency	50 - 60 Hz	CPU power cable length	60 cm
Input current	12 A	ATX power connector (20+4 pin)	✓
Power Factor Correction (PFC) type	Active	Floppy drive power connector	1
Combined power (+3.3V)	105 W	Floppy disk drive connector	✓
Combined power (+12V)	732 W	Floppy disk drive cable length	15 cm
Combined power (+5V)	105 W	Cabling type	Fully-Modular
Combined power (-12V)	3.6 W	Performance	
Combined power (+5Vsb)	15 W	80 PLUS certification *	80 PLUS Gold
Max output current (+3.3V)	20 A	Purpose *	PC
Max output current (+12V)	61 A	Power supply unit (PSU) form factor *	ATX
Max output current (+5V)	20 A	ATX version	2.31
Max output current (-12V)	2.3 A	Bearing technology	HYB
Max output current (+5Vsb)	3 A	Mean time between failures (MTBF)	100000 h
Hold time	16 ms	Design	
Efficiency	90%	Product colour	Black
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	Cooling type	Active
Ports & interfaces		Fan diameter	12 cm
Motherboard power connector *	20+4 pin ATX	Number of fans	1 fan(s)
Motherboard power cable length	61 cm	Fan location	Top
Number of SATA power connectors	8	On/off switch	✓
SATA power cable length	150,300,450,600 mm	Packaging content	
Peripheral (Molex) power connectors (4-pin) *	3	Cables included	CPU, PCIe, Peripheral (Molex), SATA
Peripheral (Molex) power cable length	120,500 mm	Weight & dimensions	
		Width	150 mm

Ports & interfaces		Weight & dimensions	
EPS power connector (4+4 pin)	✓	Depth	140 mm
PCI Express power connectors (6+2 pin)	4	Height	86 mm
Logistics data			
		Harmonized System (HS) code	84733020



4719331552671

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date