

Lenovo ThinkSystem SR630 V2 servidor 2.88 TB Bastidor (1U) Intel® Xeon Silver 4310 2.1 GHz 256 GB DDR4-SDRAM 750 W

Marca : LenovoFamilia de productos:
ThinkSystemCódigo del producto:
7Z71A07XLA

Nombre del producto: SR630

V2



Lenovo ThinkSystem SR630 V2. Familia de procesador: Intel® Xeon Silver, Frecuencia del procesador: 2.1 GHz, Modelo del procesador: 4310. Memoria interna: 256 GB, Tipo de memoria interna: DDR4-SDRAM, Diseño de memoria (ranuras x tamaño): 16 x 16 GB. Capacidad total de almacenaje: 2.88 TB. Ethernet. Fuente de alimentación: 750 W, Suministro de energía redundante (RPS), soporte. Tipo de chasis: Bastidor (1U)

| Processor | | Design | |
|---|--|--|--|
| Processor manufacturer * Processor family * Processor model * Processor frequency * Processor boost frequency Processor cache Number of processors installed Maximum number of SMP processors | Intel Intel Xeon Silver 4310 2.1 GHz 3.3 GHz 18 MB 2 | Chassis type * Product colour Rack mounting Redundant fans support | Rack (1U) Black ✓ |
| | | Performance | |
| | | Performance management Noise level BIOS type | XClarity Enterprise 56 dB UEFI |
| Memory | | Trusted Platform Module (TPM) | ✓ |
| Internal memory * Internal memory type * | 256 GB DDR4-SDRAM | Trusted Platform Module (TPM) version | 2.0 |
| Memory slots | 32x DIMM | Software | |
| ECC | ✓ | Operating system installed * | × |
| Memory clock speed Memory layout (slots x size) | 3200 MHz 16 x 16 GB | Mic | Microsoft Windows Server 2016 Microsoft Windows Server 2019 Microsoft Windows Server 2022 Red |
| Storage | | | Hat Enterprise Linux 7.9 Red Hat |
| | 3 960 GB | Compatible operating systems * | Enterprise Linux 8.2 Red Hat Enterprise Linux 8.3 SUSE Linux Enterprise Server 12 SP5 SUSE Linux Enterprise Server 12 Xen SP5 SUSE Linux Enterprise Server 15 SP2 SUSE Linux Enterprise Server 15 Xen SP2 VMware ESXi 6.7 U3 VMware ESXi 7.0 U2 |
| Optical drive type * | × | Power | |
| Internal drive bays | 8 | Redundant power supply (RPS) support * | ✓ |
| Graphics | | Power supply * | 750 W |
| Maximum graphics card memory | 16 MB | Number of redundant power | 2 |
| Network | | supplies supported Number of redundant power | |
| Wake-on-LAN ready | ✓ | supplies installed | 2 |
| Ethernet LAN | ✓ | Operational conditions | |
| Ports & interfaces | | Storage temperature (T-T) Storage relative humidity (H-H) | -40 - 60 °C 8 - 90% |
| USB 2.0 ports quantity USB 3.2 Gen 1 (3.1 Gen 1) Type-A | 1 | , , , | 0 - 30 /u |
| ports quantity | 4 | Weight & dimensions | 440 |
| VGA (D-Sub) ports quantity | 2 | Width Depth Height | 440 mm 773 mm 43 mm |

