

## Hikvision Digital Technology DS-7232HGHI-M2 videgrabadora digital Negro

**Marca :** Hikvision Digital Technology

**Código del producto:** DS-7232HGHI-M2

**Nombre del producto :** DS-7232HGHI-M2



32-ch 720p 1U H.265 DVR

Hikvision Digital Technology DS-7232HGHI-M2 videgrabadora digital Negro:

Desde su lanzamiento en 2013, los productos analógicos de la serie Turbo HD de Hikvision han sido aplaudidos en todo el mundo por sus increíbles capacidades. Hikvision presenta su nuevo Turbo HD GT, la más reciente iteración de Turbo, que lleva la serie a niveles más amplios, más rápidos y más fuertes, y ofrece más innovaciones y logros tecnológicos a nuestros clientes. La nueva línea Turbo HD GT ha llegado con tres grandes jugadores.

| Desempeño                                      |                                            | Puertos e Interfaces                                 |                                                                                               |
|------------------------------------------------|--------------------------------------------|------------------------------------------------------|-----------------------------------------------------------------------------------------------|
| Máxima resolución de video                     | 1920 x 1080 Pixeles                        | Puertos de salida VGA (D-Sub)                        | 1                                                                                             |
| Formatos de compresión de video                | H.264, H.264+, H.265, H.265+               | Cantidad de puertos tipo A USB 3.2 Gen 1 (3.1 Gen 1) | 2                                                                                             |
| Formatos de audio soportados                   | G.711 µ-law                                | Puertos RS-485                                       | 1                                                                                             |
| Interno                                        | ✗                                          | <b>Red</b>                                           |                                                                                               |
| Velocidad de captura ed video (PAL)            | 30 fps                                     | Ethernet                                             | ✓                                                                                             |
| Velocidad de captura ed video (NTSC)           | 30 fps                                     | Tipo de interfaz ethernet                            | Ethernet rápido, Gigabit Ethernet                                                             |
| Resoluciones de reproducción soportadas        | 1080p lite/720p/720p lite/WD1/4CIF/VGA/CIF | Puertos Ethernet LAN (RJ-45)                         | 1                                                                                             |
| Cantidad de canales                            | 32 canales                                 | Protocolos de red compatibles                        | TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF, EHome |
| Color del producto *                           | Negro                                      | <b>Disco duro</b>                                    |                                                                                               |
| Señal analógica                                | NTSC, PAL                                  | Número de HDDs soportados                            | 2                                                                                             |
| Indicadores LED                                | ✓                                          | Interfaz del HDD                                     | SATA III                                                                                      |
| Canales de salida de audio                     | 1.0 canales                                | Capacidad máxima del HDD                             | 10000 GB                                                                                      |
| Velocidad máxima de cuadro                     | 30 fps                                     | <b>Control de energía</b>                            |                                                                                               |
| Emisión de vídeo                               | ✓                                          | Tipo de fuente de alimentación                       | CC                                                                                            |
| Transmisión de audio                           | ✓                                          | Voltaje CD                                           | 12 V                                                                                          |
| Compatible con transmisión dual                | ✓                                          | <b>Peso y dimensiones</b>                            |                                                                                               |
| Rango de bits                                  | 64 Kbit/s                                  | Ancho                                                | 380 mm                                                                                        |
| Número de canales reproducidos simultáneamente | 16 canales                                 | Profundidad                                          | 320 mm                                                                                        |
| <b>Puertos e Interfaces</b>                    |                                            | Altura                                               | 48 mm                                                                                         |
| Canales de entrada de alarma                   | 1                                          | Peso                                                 | 2.2 kg                                                                                        |
| Canales de salida de alarma                    | 1                                          | <b>Condiciones ambientales</b>                       |                                                                                               |
| puertos de entrada BNC                         | 32                                         | Intervalo de temperatura operativa (T-T)             | -10 - 55 °C                                                                                   |
| puertos de salida BNC                          | 1                                          | Intervalo de humedad relativa para funcionamiento    | 10 - 90%                                                                                      |
| Número de puertos HDMI                         | 1                                          |                                                      |                                                                                               |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-APR-2023. Prints or copies of Information are only valid on the printed Publication date