QNAP

QNAP TS-462-4G servidor NAS o de almacenamiento Tower Intel® Celeron® N4505 4 GB DDR4 0 TB QNAP QTS Blanco

Marca : QNAP Código del producto: TS-462-4G

Nombre del producto: TS-462-4G

Maximum RAM supported

16 GB

QNAP TS-462-4G. Tipo: NAS. Tipo de chasis: Tower. Clase del dispositivo: Hogar y oficina en el hogar. Familia de procesador: Intel® Celeron®, Modelo del procesador: N4505, Frecuencia del procesador: 2 GHz. Memoria interna: 4 GB, Tipo de memoria interna: DDR4. Capacidad de almacenamiento total instalado: 0 TB. Sistema operativo instalado: QNAP QTS





Storage		Performance	
Storage drive capacity *	0 GB	Type *	NAS
Supported storage drive interfaces	Serial ATA III	Device class *	Home & Home Office
Storage drive sizes supported	3.5,M.2,2.5	Backup function *	✓
Number of M.2 (M & B) slots	2	Backup features	Cloud, iSCSI LUN
RAID support *	✓	Buzzer	✓
RAID levels	0, 1, 5, 6, 10, JBOD	Multilingual support	✓
Online RAID migration	✓	Snapshot	✓
Online RAID expansion	✓	Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SSI
RAID rebuild	✓	Access Control List (ACL)	✓
Hot-swap drive bays	1	Reset button	✓
Supported file systems	FAT32, HFS+, NTFS, exFAT, ext3,	On/off switch	/
,	ext4	Built-in FTP server	/
Storage drives installed * Total installed storage capacity *	X 0 TB	Browser supported	Apple Safari, Google Chrome, Microsoft Edge, Mozilla Firefox
Number of storage drives supported	4	System log	✓
Installed storage drive type *	×	Hot spare	✓
Supported storage drive types *	HDD & SSD	Password authentication	✓
Bad block scan	✓	Disk scan	✓
Disk roaming	1	S.M.A.R.T. support	/
		Share folder	/
Processor	Litel	USB copy function	/
Processor manufacturer * Processor family *	Intel® Celeron®	Software	
Processor model *	N4505	Operating system installed *	QNAP QTS
Processor frequency *	2 GHz	Operating system version	5.0.1
Processor boost frequency Processor cores	2.9 GHz 2	Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8
Processor threads	2	Linux operating systems supported	✓
CPU configuration (max)	1		Mac OS X 10.10 Yosemite, Mac OS
Number of processors supported	1		10.12 Sierra, Mac OS X 10.13 High
On-board graphics card model	Intel® UHD Graphics	Mac operating systems supported	Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey
Memory			
Internal memory *	4 GB		Jul, Mac O3 A 12.0 Monteley
Internal memory type	DDR4		
M. C. DAM	16 CD		

Memory		Software	
Memory	2	Suitware	Windows Comer 2000 D2 W/
Memory slots Memory form factor Flash memory	2 SO-DIMM 4000 MB	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Network		Power	
Ethernet LAN *	✓	Power supply location	External
Ethernet LAN data rates	10,100,1000,2500 Mbit/s	Power supply unit (PSU) capacity	90 W
DHCP server	✓	Number of power supply units	1
Jumbo frames support	✓	Power consumption (typical)	25.98 W
iSCSI support	✓	Power consumption (sleep)	11.3 W
Wake-on-LAN ready	✓	AC input voltage	100 - 240 V
Dynamic DNS (DDNS)	✓	Fan voltage	12 V
Ports & interfaces		Weight & dimensions	
USB port *	1	Width *	170 mm
USB 2.0 ports quantity	2	Depth *	226 mm
USB 3.2 Gen 2 (3.1 Gen 2) Type-A		Height * Weight	168 mm 2.26 kg
ports quantity	2	Package weight	3.6 kg
HDMI ports quantity	1	5 5	3.0 kg
HDMI version	2.0	Packaging content	AC LAN (DLAF)
Ethernet LAN (RJ-45) ports *	1	Cables included Power cables quantity	AC, LAN (RJ-45) 1
Design			1
Chassis type *	Tower	Processor special features	
Cooling type *	Active	Enhanced Intel SpeedStep Technology	✓
Product colour Number of fans	White	Idle States	/
Fan diameter	1 fan(s) 12 cm	Intel 64	1
LED indicators	HDD, LAN, Power, Status, USB	Intel Trusted Execution Technology	X
Cable lock slot	✓	Intel Virtualization Technology (VT-x)	·
Cable lock slot type	Kensington	Intel Virtualization Technology for Directed I/O (VT-d)	•
		Intel VT-x with Extended Page Tables (EPT)	/
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H)	0 - 40 °C 5 - 95% -20 - 70 °C 5 - 95%



4711103080030

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.