GIGABYTE[®]

GIGABYTE GP-P650G-US unidad de fuente de alimentación 650 W 20+4 pin ATX ATX Negro

Marca : GIGABYTE

Código del producto: GP-P650G-US

Nombre del producto : GP-P650G-US

GIGABYTE GP-P650G-US. Potencia total: 650 W, Voltaje de entrada AC: 100 - 240 V, Corriente de entrada: 12 - 6 A. Alimentador de energía para tarjeta madre: 20+4 pin ATX, Longitud del cable de alimentación de la placa base: 50 cm, Longitud del cable de alimentación SATA: 150,500 mm. Utilizar con: PC, Factor de forma de fuente de alimentación (PSU): ATX, Certificación 80 PLUS: 80 PLUS Bronze. Color del producto: Negro, Tipo de enfriamiento: Activo, Diámetro de ventilador: 12 cm. Ancho: 140 mm, Profundidad: 150 mm, Altura: 86 mm





Power		Ports & interfaces	
Total power * AC input voltage * Input current Maximum input current (@110V) Maximum input current (@220V) Power Factor Correction (PFC) type Combined power (+3.3V) Combined power (+12V) Combined power (+12V) Combined power (+5V) Combined power (+5Vsb) Max output current (+3.3V) Max output current (+12V) Max output current (+12V) Max output current (+5Vsb)	650 W 100 - 240 V 12 - 6 A 12 A 6 A Active 120 W 650 W 650 W 650 W 3.6 W 12.5 W 20 A 54.17 A 20 A 0.3 A 20 A	Ports & Interfaces CPU power cable length ATX power connector (20+4 pin) Floppy disk drive connector Cabling type Performance 80 PLUS certification * Purpose * Power supply unit (PSU) form factor * ATX version Noise level Bearing technology Mean time between failures (MTBF) Design Product colour Cooling type	60 cm 60 cm 1 1 1 Non-Modular 1 80 PLUS Bronze PC ATX 2.31 39 dB HDB 100000 h Black Active
Power protection features Ports & interfaces	circuit, Under voltage	Fan diameter Number of fans	12 cm 1 fan(s)
Motherboard power connector * Motherboard power cable length	20+4 pin ATX 50 cm	Fan location On/off switch	Top ✓
Number of SATA power connectors SATA power cable length Peripheral (Molex) power connectors (4-pin) * Peripheral (Molex) power cable	6 150,500 mm 3 150,500 mm	Weight & dimensionsWidth140 mmDepth150 mmHeight86 mm	150 mm
length PCI Express power connectors (6+2 pin) PCI Express power cable length	4 65 cm	Packaging data Package type	Box

Ports & interfaces		Logistics data	
CPU P4 connector (4-pin)	1	Harmonized System (HS) code	84733020
CPU power connector (4+4 pin)	•	Other features	
		Noise level (silent mode, <30%)	20 dB
		Noise level (quiet mode, 50%)	29 dB
		Noise level (full-load mode, 100%)	39 dB
		Power management	J

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.