ASUS TUF Gaming B760-Plus WIFI Intel B760 LGA 1700 ATX

Marca : ASUS

Código del producto: 90MB1ER0-M0EAY0

Nombre del producto : TUF Gaming B760-Plus WIFI

- Socket Intel® LGA 1700: Listo para procesadores intel de 13a y 12a generación

 Solución de energía mejorada: 12+1 DrMOS, PCB de seis capas, conectores ProCool, chokes de aleación y capacitores duraderos para una entrega de energía estable y ultilidad Fan Xpert 4
Enfriamiento completo: Disipador de calor VRM grande, disipadores de calor M.2, disipador de calor PCH, puertos para ventilador híbrido y Fan Xpert 2+

- Conectividad más reciente: Puerto PCIe 5.0, puertos PCIe 4.0 M.2, USB 3.2 Gen 2x2 Type-C posterior®, puerto para panel frontal USB 3.2 Gen 2 Type-C® ; y compatibilidad con Thunderbolt 4[™] (USB4®) - Cancelación de ruido de IA bidireccional: Reduce el ruido de fondo del micrófono y la salida de audio para una comunicación nítida en juegos o videoconferencias

Intel B760, Socket LGA1700, 4 x DIMM, Max. 192GB DDR5, Realtek 2.5Gb Ethernet, 802.11 a/b/g/n/ac/ax, 128 Mb Flash ROM, UEFI AMI BIOS, ATX





| Duccescu | | Deer nevel 1/0 nevte | |
|--|---|--|---|
| Processor | | Rear panel I/O ports | |
| Processor manufacturer * Processor socket * | Intel LGA 1700 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * | 1 |
| Compatible processor series * | Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7 | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity * | 2 |
| Maximum number of SMP processors | 1 | USB 3.2 Gen 2x2 Type-C ports quantity | 1 |
| Supported processor sockets | LGA 1700 | Ethernet LAN (RJ-45) ports * | 1 |
| Memory | | VGA (D-Sub) ports quantity * | 1 |
| Supported memory types * | DDR5-SDRAM | HDMI ports quantity * | 1 |
| Number of memory slots * | UDR5-SDRA™ 4 | HDMI version | 2.1 |
| , | 4 DIMM | DisplayPorts quantity | 1 |
| Memory slots type | | DisplayPort version | 1.4 |
| Memory channels | Dual-channel | Headphone outputs | 1 |
| ECC compatibility | Non-ECC | Line-in | 1 |
| Supported memory clock speed (max) | 5066 MHz | Network | |
| Maximum internal memory * | 128 GB | Ethernet LAN | 1 |
| Unbuffered memory | 1 | Ethernet interface type | 2.5 Gigabit Ethernet |
| Storage controllers | | Wi-Fi * | ✓ |
| Supported storage drive types | HDD & SSD | Top Wi-Fi standard | Wi-Fi 6E (802.11ax) |
| Supported storage drive interfaces * | 5.0, SATA III | Wi-Fi standards | 802.11a, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax) |
| Number of HDDs supported | 4 | Bluetooth | |
| Number of storage drives supported | 7 | Bluetooth version | 5.2 |
| RAID support | 1 | | J.2 |
| RAID levels | 0, 1, 5, 10 | Features | |
| Graphics | | Motherboard chipset * | Intel B760 |
| Parallel processing technology | Not supported | Audio output channels * | 7.1 channels |
| support * | Not supported | Product colour | Black |
| | | Component for * | PC |

| Graphics | | Features | |
|---|---|---|------------------------|
| On-board graphics card | × | Motherboard form factor * | ATX |
| Internal I/O | | Motherboard chipset family * | Intel |
| USB 2.0 connectors * | 2 | Cooling type | Passive ATX |
| USB 3.2 Gen 1 (3.1 Gen 1) connectors * | 2 | Power source type Windows operating systems supported | Windows 10, Windows 11 |
| Number of SATA III connectors * | 4 | | |
| S/PDIF out connector | 1 | Expansion slots | |
| Front panel audio connector | 1 | PCI Express x1 (Gen 3.x) slots | 2 |
| Front panel connector | 1 | PCI Express x16 (Gen 4.x) slots | 1 |
| ATX Power connector (24-pin) | 1 | PCI Express x16 (Gen 5.x) slots | 1 |
| CPU fan connector | | PCI slots | 4 |
| Number of chassis fan connectors | 3 | Number of M.2 (M) slots | 3 |
| Peripheral (Molex) power | | BIOS | |
| connectors (4-pin) | 1 | BIOS type * | UEFI AMI |
| EPS power connector (8-pin) | 1 | BIOS memory size | 128 Mbit |
| Number of COM connectors | 1 | Packaging data | |
| TPM connector | 1 | Package width | 328 mm |
| Thunderbolt headers | 1 | Package depth | 266 mm |
| 12V power connector | 1 | Package height | 53 mm |
| RGB LED pin header | ✓ | Package weight | 1.16 kg |
| Rear panel I/O ports | | Weight & dimensions | |
| USB 2.0 ports quantity * | 2 | Width | 305 mm |
| | | Depth | 244 mm |
| | | Packaging content | |
| | | | |

Cables included

SATA





4711387095119

0197105095113



197105095113

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.