Canon

Canon EOS Rebel T7 EF-S 18-55mm f/3.5-5.6 III + 75- 300MM f/4 5.6 III Juego de cámara SLR 24.1 MP CMOS 6000 x 4000 Pixeles Negro

Marca : Canon

Familia de productos: EOS

Código del producto: 23727C084

Nombre del producto : EOS Rebel T7 EF-S 18-55mm f/3.5-5.6 III + 75- 300MM f/4 5.6 III

24.1 Mpix (25.8 Mpix Total), CMOS, 3.72µm, TTL, E-TTL II, 3" TFT, PictBridge, Hi-Speed USB, Type C, Wi-fi, NFC, 485g

Canon EOS Rebel T7 EF-S 18-55mm f/3.5-5.6 III + 75- 300MM f/4 5.6 III Juego de cámara SLR 24.1 MP CMOS 6000 x 4000 Pixeles Negro:

La EOS Rebel T7 es la cámara ideal para quienes disfrutan capturar recuerdos en sus dispositivos móviles, pero buscan dar el siguiente paso y mejorar la calidad de imagen en sus fotografías.

Obtendrás imágenes de alta calidad incluso en momentos de poca iluminación.
Excelente para captar la ciudad de noche o las risas de tus amigos mientras estás acampando en el bosque.

Conectividad Wi-Fi y NFC
Comparte tus fotos y videos entre cámaras, imprime imágenes o publica tus recuerdos y obras maestras en redes sociales al instante usando Wi-Fi® y la aplicación gratuita Camera Connect.*

La función de Comunicación de Campo Cercano (NFC) brinda conexión sencilla con teléfonos Android™ compatibles**, y con el dispositivo Connect Station CS100. Solo toca el dispositivo con la T7 y comienza a transferir.

Picture quality	
Camera type *	SLR Camera Kit
Megapixel (approx.) *	24.1 MP
Sensor type *	CMOS
Maximum image resolution *	6000 x 4000 pixels
Still image resolution(s) *	6000 x 4000, 3984 x 2656, 2976 x 1984, 2400 x 1600, 5328 x 4000, 3552 x 2664, 2656 x 1992, 2112 x 1600, 6000 x 3368, 3984 x 2240, 2976 x 1680, 2400 x 1344, 4000 x 4000, 2656 x 2656, 1984 x 1984, 1600 x 1600
Image stabilizer *	✔
Supported aspect ratios	1:1, 3:2, 4:3, 16:9
Total megapixels	25.8 MP
Image sensor size (W x H)	22.3 x 14.9 mm
Sensor format	Advanced Photo System type-C (APS-C)
Image formats supported *	RAW
Lens system	
Focal length range	18 - 55 mm
Minimum aperture number	4
Maximum aperture number	5.6
Lens structure (elements/groups)	12/10
Filter size	58 mm
Lens 2 focal length range	75 - 300 mm
Focusing	
Focus *	TTL
Focus adjustment *	Auto/Manual

Memory	
Compatible memory cards *	SD, SDIO, SDXC
Memory slots	1
Display	
Display *	LCD
Touchscreen *	✕
Display diagonal *	7.62 cm (3")
Display resolution (numeric)	1040000 pixels
Flip-out screen	✔
Vari-angle LCD display	✔
Viewfinder	
Viewfinder type	Electronic
Magnification	0.8x
Ports & interfaces	
PictBridge *	✔
USB version *	2.0
HDMI *	✔
HDMI connector type	Micro
Network	
Wi-Fi *	✔
Near Field Communication (NFC) *	✔
Camera	
White balance *	Auto, Cloudy, Custom modes, Flash, Shade, Tungsten
Scene modes *	Close-up (macro), Food, Landscape, Night portrait, Portrait, Sports

Focusing	
Auto focusing (AF) modes *	AI Focus, One Shot Focus, Single Auto Focus
Auto Focus (AF) lock	✔

Exposure	
ISO sensitivity (min) *	100
ISO sensitivity (max) *	51200
ISO sensitivity	100, 200, 400, 800, 1600, 3200, 6400, 12800, 25600, 51200
Light exposure modes *	Aperture priority AE, Auto, Manual
Light exposure correction *	± 3EV (1/2EV; 1/3EV step)
Light metering *	Centre-weighted, Partial
Auto Exposure (AE) lock	✔

Shutter	
Fastest camera shutter speed *	1/4000 s
Slowest camera shutter speed *	30 s
Camera shutter type	Mechanical

Flash	
Flash modes *	Auto, Fill-in, Pre-flash, Red-eye reduction
Flash exposure lock	✔
Flash exposure compensation	✔
Flash exposure correction	±2EV (1/2, 1/3 EV step)
Pre-flash	✔

Video	
Video recording *	✔
Maximum video resolution *	1920 x 1080 pixels
HD type *	Full HD
Video resolutions	640 x 480,1280 x 720,1920 x 1080
Motion JPEG frame rate	59.94 fps

Audio	
Built-in microphone *	✔
Voice recording	✔

Camera	
Shooting modes *	Auto, Manual, Program, Scene
Photo effects *	Black&White, Negative film, Sepia, Vivid
Self-timer delay *	2,10 s
Contrast adjustment	✔
Brightness adjustment	✔
Camera playback	Movie, Single image, Slide show
Histogram	✔
Camera file system	DPOF, Exif 2.1
Tripod mounting supported *	✔

Design	
Product colour *	Black

Battery	
Battery technology *	Lithium-Ion (Li-Ion)
Battery voltage	7.2 V
Battery capacity	1040 mAh
Battery recharge time	8 h

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 85%

Weight & dimensions	
Width	131 mm
Depth	76.2 mm
Height	99.9 mm
Weight	85 g
Weight (including battery)	532 g

Packaging content	
Hand strap	✔
Battery charger included	✔
Batteries included	✔
Quick start guide	✔

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date