MSI G242C monitor de computadora 59.9 cm (23.6") 1920 x 1080 Pixeles Full HD Negro

Marca : MSI Código del producto: G242C

Nombre del producto: G242C

MSI G242C. Diagonal de la pantalla: 59.9 cm (23.6"), Resolución de la pantalla: 1920 x 1080 Pixeles, Tipo HD: Full HD, Tiempo de respuesta: 1 ms, Relación de aspecto nativa: 16:9, Ángulo de visión, horizontal: 178°, Ángulo de visión, vertical: 178°. montaje VESA. Color del producto: Negro





Display diagonal * 59.9 cm (23.6") Product colour * Black Display resolution * 1920 x 1080 pixels Frameless design ✓ HD type * Full HD Ports & interfaces Native aspect ratio * 16:9 Built-in USB hub * × Panel type * VA HDMI ports Quantity 2 Display brightness (typical) 250 cd/m² HDMI ports quantity 1 Response time * 1 ms HDMI ports quantity 1 Anti-glare screen ✓ DisplayPorts quantity 1 Screen shape * Curved DisplayPort squantity 1 Screen curvature rating 1500R Ergonomics Supported video modes 16:9 Panel mounting interface 7 × 75 mm Contrast ratio (typical) * 3000:1 Cable lock slot * ✓ Contrast ratio (typical) * 3000:1 Cable lock slot * ✓ Viewing angle, horizontal 178° Tilt angle range ✓ Viewing angle, borizontal 16.7 million colours Energy efficiency class (SDR) * E </th <th></th> <th></th> <th></th> <th></th>				
Display resolution* 1920 x 1080 pixels Frameless design ✓ HD type* Full HD Ports & interfaces Native aspect ratio* 16:9 Built-in USB hub* X Panel type* VA Built-in USB hub* X Touchscreen* X HDMI* ✓ Display brightness (typical) 250 cd/m² HDMI ports quantity 1 Response time* 1 ms HDMI ports quantity 1 Anti-glare screen ✓ DisplayPorts quantity 1 Screen shape* Curved Ergonomics Screen curvature rating 1500R Ergonomics Supported video modes 1080p VESA mounting* ✓ Supported video modes 1080p VESA mounting* ✓ Contrast ratio (typical)* 3000:1 Cable lock slot * ✓ Contrast ratio (typical)* 3000:1 Cable lock slot type Kensington Maximum refresh rate* 170 Hz Tilt adjustment ✓ Viewing angle, vertical 178° Tilt angle range <t< td=""><td>Display</td><td></td><td>Design</td><td></td></t<>	Display		Design	
HD type * Full HD	Display diagonal *	59.9 cm (23.6")	Product colour * Black	
Native aspect ratio * 16:9 Panel type * VA Built-in USB hub * X Touchscreen * X HDMI * X Touchscreen * X HDMI ports quantity 2 Response time * 1 ms HDMI ports quantity 2 Anti-glare screen ✓ DisplayPorts quantity 1 Screen shape * Curved DisplayPort version 1.2a Screen curvature rating 1500R Ergonmics Supported video modes 1080p VESA mounting * ✓ Spect ratio 16:9 Panel mounting interface 75 x 75 mm Contrast ratio (typical) * 3000:1 Cable lock slot * ✓ Contrast ratio (typical) * 3000:1 Cable lock slot type Kensington Maximum refresh rate * 170 Hz Tilt adjustment ✓ Viewing angle, horizontal 178° Tilt angle range 5 - 20° Viewing angle, vertical 178° Tilt angle range 5 - 20° Viewable size, horizontal 52.1 cm Energy efficiency clas	Display resolution *	1920 x 1080 pixels	Frameless design	
Native aspect ratio * 16:9 Panel type * VA Display brightness (typical) 250 cd/m² HDMI ports quantity 2 Response time * 1 ms HDMI version 1.4b Anti-glare screen	HD type *	Full HD	Ports & interfaces	
Touchscreen* X HDMI* V Display brightness (typical) 250 cd/m² HDMI version 1.4b HDMI version 1.4b Anti-glare screen V DisplayPorts quantity 1 Screen shape* Curved DisplayPorts quantity 1 Screen curvature rating 1500R Ergonmics Supported video modes 1080p VESA mounting* V=Aspect ratio 16:9 Panel mounting interface 75 x 75 mm Contrast ratio (typical)* 3000:1 Cable lock slot * V Contrast ratio (dynamic) Maximum refresh rate* 170 Hz Viewing angle, horizontal 178° Viewing angle, vertical 178° Display number of colours* Pixel pitch 0.27156 x 0.27156 mm Viewable size, horizontal 178° Display number of colours* Pixel pitch 0.27156 x 0.27156 mm Viewable size, vertical Digital horizontal frequency Digital vertical frequency 104 - 189.8 kHz Digital vertical frequency Action for the shape of the	•			
Display brightness (typical) Response time * 1 ms	Panel type *	VA		
Response time* 1 ms HDMI version 1.4b Anti-glare screen	Touchscreen *	×		
Anti-glare screen Screen shape * Curved DisplayPort version 1.2a Screen curvature rating Supported video modes Aspect ratio 16:9 Panel mounting interface To X 75 x 75 mm Contrast ratio (typical) * Contrast ratio (dynamic) Maximum refresh rate * 170 Hz Viewing angle, horizontal DisplayPort version 178 * Viewing angle, vertical DisplayPort version 10000000:1 Cable lock slot * Viewing angle, vertical Display mumber of colours * Display mumber of colours * Viewable size, horizontal Viewable size, vertical Digital horizontal frequency Digital vertical frequency Adobe RGB AC adapter output voltage Colour gamut standard Adobe RGB NVIDIA G-SYNC * AMD FreeSync * Viewable fixed on the stand of the s	Display brightness (typical)	250 cd/m ²	F 1 7	
Screen shape * Curved DisplayPort version 1.2a Screen curvature rating 1500R Frgonomics Supported video modes 1080p VESA mounting * ✓ Aspect ratio 16:9 Panel mounting interface 75 x 75 mm Contrast ratio (typical) * 3000:1 Cable lock slot * ✓ Contrast ratio (dynamic) 100000000:1 Cable lock slot type Kensington Maximum refresh rate * 170 Hz Tilt adjustment 7 Tilt adjustment 7 Tilt angle range 75 - 20° Viewing angle, horizontal 178° Tilt angle range 75 - 20° Viewing angle, vertical 178° Tilt angle range 75 - 20° Viewable size, horizontal 52.1 cm Energy efficiency class (SDR) * E Viewable size, horizontal 52.1 cm Energy consumption (SDR) per 1000 17 kWh Viewable size, vertical 29.3 cm hours * Power consumption (off) 0.3 W Digital horizontal frequency 104 - 189.8 kHz Power consumption (off) 0.3 W Digital vertical frequency 48 - 170 Hz AC input voltage 100 - 240 V Colour gamut standard Adobe RGB AC adapter output voltage 20 V Colour gamut standard Adobe RGB AC adapter output voltage 20 V Colour gamut standard Adobe RGB AC adapter output voltage At o G SRGB coverage (typical) 113% Weight & dimensions Performance Width (with stand) 537.4 mm NVIDIA G-SYNC * X AMD FreeSync * Height (with stand) 215.6 mm Height (with stand) 33 kg	Response time *	1 ms		
Screen curvature rating 1500R Figure 1500R VESA mounting * Aspect ratio 16:9 Panel mounting interface 75 x 75 mm Contrast ratio (typical) * Contrast ratio (dynamic) 100000000:1 Cable lock slot * Contrast ratio (dynamic) 178° Tilt adjustment Viewing angle, horizontal 178° Tilt angle range 75 x 20° Display number of colours * Display	Anti-glare screen	✓	-121 2	
Supported video modes 1080p VESA mounting * ✓ Aspect ratio 16:9 Panel mounting interface 75 x 75 mm Contrast ratio (typical) * 3000:1 Cable lock slot * ✓ Contrast ratio (dynamic) Maximum refresh rate * 170 Hz Viewing angle, horizontal Viewing angle, vertical Display number of colours * 16.7 million colours Power Pixel pitch 0.27156 x 0.27156 mm Energy efficiency class (SDR) * Energy consumption (SDR) per 1000 Nours * Digital horizontal frequency 104 - 189.8 kHz Power consumption (off) 0.3 W Digital vertical frequency 48 - 170 Hz AC input voltage 100 - 240 V Colour gamut standard Adobe RGB AC adapter output voltage 20 V Colour gamut standard Adobe RGB AC adapter output voltage 20 V Colour gamut SRGB coverage (typical) 113% Weight & dimensions Weight & dimensions Weight & stand) 414.7 mm Weight (with stand) 414.7 mm Weight (with stand) 43 3 8 a	Screen shape *	Curved	DisplayPort version 1.2a	
Aspect ratio 16:9 Panel mounting interface 75 x 75 mm Contrast ratio (typical) * 200000000:1 Contrast ratio (dynamic) Maximum refresh rate * 170 Hz Viewing angle, horizontal Viewing angle, vertical Display number of colours * Pixel pitch Viewable size, horizontal 29.3 cm Digital horizontal frequency Digital vertical frequency Colour depth Colour gamut standard Adobe RGB RGB coverage (typical) AMD FreeSync * Maximum refresh rate * 170 Hz Cable lock slot type Kensington Kensington Kensington Kensington Fower Tilt adjustment Filt angle range Tilt angle range Tilt angle range Fower Fower Fower Fower Finergy efficiency class (SDR) * E Fenergy consumption (SDR) per 1000 17 kWh hours * Power consumption (off) 0.3 W 17 kWh 17 kWh 17 kWh 18 bit 19 you current 100 - 240 V	Screen curvature rating	1500R	Ergonomics	
Contrast ratio (typical)* 3000:1 Contrast ratio (dynamic) Maximum refresh rate* 170 Hz Viewing angle, horizontal Display number of colours* Pixel pitch Viewable size, horizontal 170 Hz 170 Hz Viewable size, vertical Digital horizontal frequency Digital vertical frequency Colour depth Colour gamut SRGB coverage (typical) 113% Partial midming interface Cable lock slot * Cable lock slot type Kensington Tilt adjustment Venery Tilt adjustment Venery Tilt angle range To verer Tilt adjustment Venery Tilt adjustment Venery Tilt adjustment Venery Tilt angle range To verer Tilt adjustment Venery To Ven	Supported video modes	1080p	VESA mounting * ✓	
Contrast ratio (typical) * 3000:1 Cable lock slot *	Aspect ratio	16:9	Panel mounting interface 75 x 75	mm
Maximum refresh rate * 170 Hz Viewing angle, horizontal 178° Viewing angle, vertical 178° Display number of colours * 16.7 million colours Pixel pitch 0.27156 x 0.27156 mm Viewable size, horizontal 52.1 cm Viewable size, vertical 29.3 cm Digital horizontal frequency 104 - 189.8 kHz Digital vertical frequency 48 - 170 Hz Colour depth 8 bit 1nput current 2.25 A Colour gamut standard Adobe RGB AC adapter output voltage 20 V Colour gamut standard 91% SRGB coverage (typical) 113% Performance NVIDIA G-SYNC * X AMD FreeSync * Viewable size, horizontal 178° Tilt adjustment 7 (It adjustment 7 (It adjustment) 8 (It adjustment) 9 (It adjustment)		3000:1		
Maximum refresh rate * 170 Hz Viewing angle, horizontal 178° Viewing angle, vertical 178° Display number of colours * 16.7 million colours Power Pixel pitch 0.27156 x 0.27156 mm Energy efficiency class (SDR) * E Viewable size, horizontal 52.1 cm Energy consumption (SDR) per 1000 hours * Digital horizontal frequency 104 - 189.8 kHz Power consumption (off) 0.3 W Digital vertical frequency 48 - 170 Hz AC input voltage 100 - 240 V Colour depth 8 bit Input current 2.25 A Colour gamut standard Adobe RGB AC adapter output voltage 20 V Colour gamut 91% Energy efficiency scale A to G SRGB coverage (typical) 113% Weight & dimensions Performance Width (with stand) 537.4 mm AMD FreeSync * Weight (with stand) 414.7 mm Weight (with stand) 414.7 mm Weight (with stand) 3 3 km	Contrast ratio (dynamic)		Cable lock slot type Kensing	con
Viewing angle, horizontal Viewing angle, vertical Display number of colours * Pixel pitch Viewable size, horizontal Viewable size, vertical Digital horizontal frequency Digital vertical frequency Colour depth Colour gamut standard Colour gamut SRGB coverage (typical) Power Tilt angle range -5 - 20° Power Energy efficiency class (SDR) * E Energy consumption (SDR) per 1000 17 kWh 17 kWh 17 kWh 18 bit Power consumption (off) 0.3 W AC input voltage 100 - 240 V 101 claurent 2.25 A Colour gamut standard Adobe RGB AC adapter output voltage 20 V Energy efficiency scale A to G Weight & dimensions Performance NVIDIA G-SYNC * AMD FreeSync * Viewable size, vertical Power Energy efficiency scale A to G Width (with stand) 215.6 mm Height (with stand) 414.7 mm Weight (with stand) 43 kg			7.	
Display number of colours * 16.7 million colours Power Pixel pitch 0.27156 x 0.27156 mm Energy efficiency class (SDR) * E Viewable size, horizontal 52.1 cm Energy consumption (SDR) per 1000 Viewable size, vertical 29.3 cm hours * Digital horizontal frequency 104 - 189.8 kHz Power consumption (off) 0.3 W Digital vertical frequency 48 - 170 Hz AC input voltage 100 - 240 V Colour depth 8 bit Input current 2.25 A Colour gamut standard Adobe RGB AC adapter output voltage 20 V Colour gamut 91% Energy efficiency scale A to G SRGB coverage (typical) 113% Weight & dimensions Performance Width (with stand) 537.4 mm NVIDIA G-SYNC * AMD FreeSync * Weight (with stand) 414.7 mm Weight (with stand) 414.7 mm Weight (with stand) 3 3 km	5 5		•	
Pixel pitch 0.27156 x 0.27156 mm Energy efficiency class (SDR) * E Viewable size, horizontal 52.1 cm Energy consumption (SDR) per 1000 17 kWh Viewable size, vertical 29.3 cm hours * Digital horizontal frequency 104 - 189.8 kHz Power consumption (off) 0.3 W Digital vertical frequency 48 - 170 Hz AC input voltage 100 - 240 V Colour depth 8 bit Input current 2.25 A Colour gamut standard Adobe RGB AC adapter output voltage 20 V Colour gamut 91% Energy efficiency scale A to G SRGB coverage (typical) 113% Weight & dimensions Performance Width (with stand) 537.4 mm NVIDIA G-SYNC * AMD FreeSync * Weight (with stand) 414.7 mm Weight (with stand) 33 kg			. 3 3.	
Viewable size, horizontal Viewable size, vertical Digital horizontal frequency Digital vertical frequency 104 - 189.8 kHz Digital vertical frequency 48 - 170 Hz Colour depth Colour gamut standard Colour gamut 91% Energy consumption (SDR) per 1000 17 kWh 0.3 W 100 - 240 V 100 - 240 V 100 - 240 V AC input voltage 100 - 240 V AC adapter output voltage 20 V Energy efficiency scale A to G Weight & dimensions Performance Width (with stand) NVIDIA G-SYNC* AMD FreeSync* Weight (with stand) Height (with stand) 414.7 mm Weight (with stand) 3 3 kg				
Viewable size, vertical Digital horizontal frequency Digital vertical frequency Digital vertical frequency 48 - 170 Hz Colour depth Colour gamut standard Colour gamut 91% Energy efficiency scale At o G Weight & dimensions Performance NVIDIA G-SYNC* AMD FreeSync* NVicipht (with stand) And ours * Now on the hours * 17 kWh hours * 17 kWh hours * 18 hours * 18 hours * 19 wow consumption (off) 0.3 W 100 - 240 V 2.25 A AC adapter output voltage 20 V Energy efficiency scale A to G Weight & dimensions Width (with stand) 537.4 mm Depth (with stand) 414.7 mm Weight (with stand) AMD FreeSync * Weight (with stand) 414.7 mm	·		3, 1 1 1, 1 1, 1 1, 1	
Digital horizontal frequency 104 - 189.8 kHz Power consumption (off) 0.3 W 100 - 240 V Colour depth 8 bit Input current Colour gamut standard Adobe RGB AC adapter output voltage Colour gamut 91% Energy efficiency scale A to G Weight & dimensions Performance Width (with stand) NVIDIA G-SYNC* AMD FreeSync* Weight (with stand) Power consumption (off) 0.3 W 100 - 240 V 2.25 A AC adapter output voltage Energy efficiency scale A to G Weight & dimensions 4 to G A to G Weight (with stand) Depth (with stand) 414.7 mm Weight (with stand) 414.7 mm	,			
Digital vertical frequency 48 - 170 Hz AC input voltage 100 - 240 V Colour depth 8 bit Input current 2.25 A Colour gamut standard Adobe RGB AC adapter output voltage 20 V Colour gamut 91% Energy efficiency scale A to G sRGB coverage (typical) 113% Weight & dimensions Performance Width (with stand) 537.4 mm NVIDIA G-SYNC * X AMD FreeSync * Weight (with stand) 414.7 mm Weight (with stand) 3 3 kg	,			
Colour depth 8 bit Input current 2.25 A Colour gamut standard Adobe RGB AC adapter output voltage 20 V Colour gamut 91% Energy efficiency scale A to G sRGB coverage (typical) 113% Weight & dimensions Performance Width (with stand) 537.4 mm NVIDIA G-SYNC * X AMD FreeSync * Weight (with stand) 414.7 mm Weight (with stand) 3 3 kg			· · · · · · · · · · · · · · · · · · ·	0 V
Colour gamut standard Adobe RGB AC adapter output voltage Colour gamut 91% Energy efficiency scale At o G SRGB coverage (typical) 113% Weight & dimensions Performance NVIDIA G-SYNC* AMD FreeSync* Weight (with stand) Depth (with stand) Height (with stand) 414.7 mm Weight (with stand) 3 3 kg	, ,			.
Colour gamut 91% Energy efficiency scale A to G sRGB coverage (typical) 113% Weight & dimensions Performance Width (with stand) 537.4 mm NVIDIA G-SYNC * X Depth (with stand) 215.6 mm AMD FreeSync * Weight (with stand) 414.7 mm Weight (with stand) 33 kg	·		F	
sRGB coverage (typical) 113% Weight & dimensions Width (with stand) NVIDIA G-SYNC * AMD FreeSync * Weight (with stand) Height (with stand) 414.7 mm Weight (with stand) 3 3 kg	•			
Performance Width (with stand) Depth (with stand) 215.6 mm AMD FreeSync * Weight (with stand) 414.7 mm Weight (with stand) 3 3 kg	•			
NVIDIA G-SYNC * X Depth (with stand) 215.6 mm AMD FreeSync *		113/0		
AMD FreeSync * Height (with stand) 414.7 mm Weight (with stand) 3.3 kg				
AMD FreeSync* Weight (with stand)	NVIDIA G-SYNC *	×	- P (
AMD FreeSync type FreeSync Premium Weight (with Stand) 3.3 kg	AMD FreeSync *	✓	- 3 (Ш
	AMD FreeSync type	FreeSync Premium	weight (with Stahu) 3.3 kg	

Multimedia		Weight & dimensions	
Built-in speaker(s) *	x	Weight (without stand)	2.55 kg
Built-in camera *	×	Packaging data	
Design		Package width	614 mm
Market positioning *	Gaming	Package depth	182 mm
		Package height	416 mm
		Package weight	5.15 kg





824142288290

0824142288290

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.