

## Bosch FLEXIDOME IP 4000i Domo Cámara de seguridad IP Exterior 1920 x 1080 Pixel Techo/pared

**Marca :** Bosch

**Código del producto:** NDE-4502-A

**Nombre del producto :** FLEXIDOME IP 4000i

Bosch FLEXIDOME IP 4000i. Tipo: Cámara de seguridad IP, Colocación compatible: Exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared, Color del producto: Blanco, Factor de forma: Domo. Iluminación mínima: 0.02 Lux, Ángulo de rotación: 330°, Ángulo de visión del objetivo, horizontal: 101°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.9 mm (1 / 2.9"), Número de píxeles efectivos (A x V): 1920 x 1080 Pixel. Intervalo de longitud focal: 3 - 10 mm, Enfoque: Motorizado

<b>Performance</b>		<b>Video</b>	
Type *	IP security camera	Back Light Compensation (BLC)	✓
Placement supported *	Outdoor	Audio system	2-way
Connectivity technology *	Wired	Audio system full duplex	✓
Auto-tracking	✓	Audio formats supported	LC-AAC
Wide Dynamic Range (WDR)	✓	Signal-to-Noise Ratio (SNR)	55 dB
Day/night mode	✓	Built-in microphone	✓
Infrared (IR) cut-off filter	✓	Voice codecs	G.711
Alarm input/output	✓	Audio detection	✓
EN 60950-1 UL 60950-1 CAN/CSA-C22.2 NO. 60950-1-03 CAN/CSA-C22.2 NO. 60950-22 EN 50130-4 EN 50130-5, Class II FCC Part15 Subpart B, Class B EMC 2014/30/EU EN 55032 class B EN 55024 AS/NZS CISPR 32 ICES-003 Class B VCCI J55022 V2/V3 EN 50121-4 EN 60950-22 CE, FCC, UL, cUL, RCM, CB, VCCI, EAC		<b>Network</b>	
Certification		Ethernet LAN *	✓
		Ethernet interface type	Fast Ethernet
		Networking standards	IEEE 802.1x, IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u IPv4, IPv6, UDP, TCP, HTTP, HTTPS, RTP/ RTCP, IGMP V2/V3, ICMP, ICMPv6, RTSP, FTP, ARP, DHCP, APIPA (Auto-IP, link local address), NTP (SNTP), SNMP (V1, V3, MIB-II), 802.1x, DNS, DNSv6, DDNS (DynDNS.org, selfHOST.de, no-ip.com), SMTP, iSCSI, UPnP (SSDP), DiffServ (QoS), LLDP, SOAP, Dropbox, CHAP
<b>Design</b>		Supported network protocols	
Form factor *	Dome	Wi-Fi *	✗
Mounting type *	Ceiling/wall	Cabling technology	10/100Base-T(X)
Product colour *	White	Quality of Service (QoS) support	✓
Housing material	Polycarbonate (PC)	<b>Storage</b>	
Protection features	Impact resistant	Built-in HDD *	✗
International Protection (IP) code	IP66	Card reader integrated	✓
IK code	IK10	Compatible memory cards	MicroSD (TransFlash), MicroSDHC, MicroSDXC
Fog proof	✓	Maximum memory card size	2 TB
<b>Camera</b>		<b>Ports &amp; interfaces</b>	
Minimum illumination	0.02 lx	Ethernet LAN (RJ-45) ports	1
Angle of rotation	330°	Composite video out	1
Lens viewing angle, horizontal	101°	Microphone in	✓
Lens viewing angle, vertical	54°	Headphone outputs	1
Tilt angle range	0 - 130°	Interface	RJ-45/SMB
Pan range	0 - 350°	<b>Security</b>	
White balance	Auto, Manual	Password protection	✓
Camera shutter type	Electronic	Video motion detection	✓
Camera shutter speed	1/15000 - 1/25 s	Active tampering alarm	✓
<b>Image sensor</b>			
Number of sensors	1		
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")		
Progressive scan	✓		
Sensor type *	CMOS		
Number of effective pixels (H x V)	1920 x 1080 pixels		

<b>Lens system</b>		<b>Security</b>	
Number of lenses *	1	Security algorithms	128-bit AES, 256-bit AES, 802.1x RADIUS, HTTPS, SSH, SSL/TLS
Focal length range	3 - 10 mm	Alert notification type	E-mail, Text alert message
Focus	Motorized	Intelligent Video Surveillance (IVS) system features	Abandoned object, Crossing line, People counting
Maximum aperture number	1.3	Digital watermark	✓
<b>Night vision</b>		<b>Management features</b>	
Night vision *	✗	Web-based management	✓
<b>Video</b>		Web browser	✓
Maximum resolution *	1920 x 1080 pixels	Firmware upgradeable	✓
Total megapixels *	2 MP	Remotely operated	✓
Video compression formats	H.264, M-JPEG, H.265, HEVC	Behavior analysis	Line crossing detection, Object removal detection, Unattended baggage detection
Supported graphics resolutions	1920 x 1080 (HD 1080), 1280 x 720 (HD 720), 768 x 432, 640 x 480 (VGA), 720 x 480		
Frame rate	30 fps	<b>Power</b>	
Analog signal format system	NTSC, PAL	Power source type *	AC, DC, PoE
Video streaming	✓	AC input voltage	24 V
Noise reduction	✓	Power consumption (max)	5.55 W
Full HD	✓	Power consumption (Power over Ethernet (PoE))	6 W
Image quality adjustment	Brightness, Contrast, Saturation	DC output voltage	12
Flip & mirror	✓	<b>Operational conditions</b>	
Privacy masking	✓	Operating temperature (T-T)	-40 - 50 °C
		Storage temperature (T-T)	-40 - 70 °C
		Operating relative humidity (H-H)	5 - 100%
<b>Weight &amp; dimensions</b>		<b>Packaging content</b>	
Height	131 mm	Number of cameras *	1
Diameter	14.5 cm		
Weight	1.1 kg		



8717332999897

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.