


NETGEAR Insight Cloud Managed WiFi 6 AX1800 Dual Band Outdoor Access Point (WAX610Y) 1800 Mbit/s Blanco Energía sobre Ethernet (PoE)

Marca : NETGEAR

Código del producto: WAX610Y-100EUS

Nombre del producto : Insight Cloud Managed WiFi 6 AX1800 Dual Band Outdoor Access Point (WAX610Y)

NETGEAR Insight Cloud Managed WiFi 6 AX1800 Dual Band Outdoor Access Point (WAX610Y). Rango máximo de transferencia de datos: 1800 Mbit/s, Velocidad máxima de transferencia de datos (2.4 GHz): 600 Mbit/s, Velocidad máxima de transferencia de datos (5 GHz): 1200 Mbit/s. Algoritmos de seguridad: EAP-PEAP, EAP-TLS, EAP-TTLS, PEAP, SSID, TTLS, WPA, WPA2, WPA3. Consumo energético: 16.1 W. Ubicación: Techo, Mástil, Pared, Color del producto: Blanco, Código IP (International Protection): IP55. Tipo de antena: Interno



Características		Control de energía	
2.4 GHz *	✓	Consumo energético	16.1 W
5 GHz *	✓	Diseño	
Rango máximo de transferencia de datos *	1800 Mbit/s	Ubicación *	Techo, Mástil, Pared
Velocidad máxima de transferencia de datos (2.4 GHz)	600 Mbit/s	Color del producto *	Blanco
Velocidad máxima de transferencia de datos (5 GHz)	1200 Mbit/s	Código IP (International Protection)	IP55
Ethernet LAN, velocidad de transferencia de datos	100,1000,2500 Mbit/s	Indicadores LED	LAN, Corriente, WLAN
Estándares de red	IEEE 802.11ax, IEEE 802.3af, IEEE 802.3at	Antena	
Auto MDI / MDI-X	✓	Tipo de antena *	Interno
MIMO	✓	Peso y dimensiones	
Tipo MIMO	Multi User MIMO	Ancho	181 mm
Método de espectro disperso	OFDM, OFDMA	Profundidad	305 mm
Wi-Fi Multimedia (WMM) / (WME)	✓	Altura	34 mm
Soporte VLAN	✓	Peso	940 g
Gestión de banda ancha adaptativa	✓	Empaquetado de datos	
Seguridad		Ancho del paquete	390 mm
Algoritmos de seguridad *	EAP-PEAP, EAP-TLS, EAP-TTLS, PEAP, SSID, TTLS, WPA, WPA2, WPA3	Largo del paquete	430 mm
Filtro de direcciones MAC	✓	Alto del paquete	350 mm
Sistema de Distribución Inalámbrico Automático (WDS por sus siglas en inglés)	✓	Peso del paquete	11.7 kg
Puertos e Interfaces		Contenido del empaque	
Puertos Ethernet LAN (RJ-45) *	1	Número de productos incluidos	1 pieza(s)
Control de energía		Kit de montaje	✓
Energía sobre Ethernet (PoE) *	✓	Condiciones ambientales	
		Intervalo de temperatura operativa (T-T)	-10 - 50 °C
		Datos de logística	
		Código de Sistema de Armonización (SA)	85176990



0606449152579



606449152579

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-JUN-2023. Prints or copies of Information are only valid on the printed Publication date