tp-link

TP-Link Deco S7 (3-pack) Doble banda (2,4 GHz / 5 GHz) Wi-Fi 5 (802.11ac) Blanco, Negro Interno

Marca : TP-Link

Nombre del producto : Deco S7 (3-pack)

Código del producto: DECO S7(3-PACK)

TP-Link Deco S7 (3-pack). Color del producto: Blanco, Negro, Tipo de antena: Interno, Tipo de producto: Sistema de malla. Banda Wi-Fi: Doble banda (2,4 GHz / 5 GHz), Máximo estándar Wi-Fi: Wi-Fi 5 (802.11ac), Tasa de transferencia de datos WLAN (máx.): 1900 Mbit/s. Seguridad con cortafuegos: SPI, Sistemas operativos móviles soportados: Android, iOS. Voltaje de entrada AC: 100 - 240 V, Frecuencia de entrada AC: 50 - 60 Hz, Voltaje de salida de adaptador AC: 12 V. Certificados de cumplimiento: RoHS, CE, Certificación: CE, FCC, RoHS, NCC, BSMI, JRF, JPA, VCCI

Design

Product type	Mesh system
Product colour *	White, Black
LED indicators	Yes
Antenna type *	Internal
Antennas quantity	3
Antenna direction type	Omni-directional
Transmit power	FCC: <30 dBm (2.4 GHz), <30 dBm (5 GHz) CE: <20 dBm (2.4 GHz), <23 dBm (5 GHz)
Reset button	✔

Wireless LAN features

Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)
Top Wi-Fi standard *	Wi-Fi 5 (802.11ac)
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
WLAN data transfer rate (max) *	1900 Mbit/s
WLAN data transfer rate (first band)	600 Mbit/s
WLAN data transfer rate (second band)	1300 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Security algorithms	WPA, WPA2
Number of guest networks (5 GHz)	1
Number of guest networks (2.4 GHz)	1
Point-to-point protocol over Ethernet (PPPoE)	✔
Dynamic IP	✔
Static IP	✔

Features

Mobile operating systems supported	Android, iOS
Universal Plug and Play (UPnP)	✔
Parental control	✔
MU-MIMO technology	✔
MIMO	✔

Ports & interfaces

Ethernet LAN (RJ-45) ports *	3
DC-in jack	✔

Power

AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
AC adapter output voltage	12 V

Certificates

Compliance certificates	RoHS, CE
Certification	CE, FCC, RoHS, NCC, BSMI, JRF, JPA, VCCI

Sustainability

Sustainability compliance	✔

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	90.7 mm

Wireless LAN features

IGMP proxy	✔
IGMP snooping	✔
Dynamic DNS (DDNS)	✔
Guest access	✔

Features

Port forwarding	✔
Firewall security	SPI
BeamForming	✔
DHCP client	✔
DHCP server	✔

Weight & dimensions

Depth	90.7 mm
Height	162.3 mm

Packaging content

Number of products included	3 pc(s)
AC adapter included	✔
Number of units included	3 pc(s)
Ethernet cable	✔

Packaging data

Package width	348 mm
Package depth	213 mm
Package height	160 mm
Package weight	1.73 kg

4897098681480

6935364073022