



Dahua Technology DH-XVR1B08-I videgrabadora digital Negro

Marca : Dahua Technology

Código del producto: DH-XVR1B08-I

Nombre del producto : DH-XVR1B08-I



Dahua Technology DH-XVR1B08-I. Color del producto: Negro, Máxima resolución de video: 1920 x 1080 Pixeles, Formatos de compresión de video: H.264, H.264+, H.265, H.265+. Tipo de interfaz ethernet: Ethernet rápido, Protocolos de red compatibles: HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter ,DDNS, FTP, Alarm..., Número de usuarios: 128 usuario(s). Interfaz del HDD: SATA, Capacidad máxima del HDD: 6 TB. Tipo de fuente de alimentación: CC, Voltaje CD: 12 V. Ancho: 198 mm, Profundidad: 202.9 mm, Altura: 41.5 mm

Desempeño		Red	
Máxima resolución de video	1920 x 1080 Pixeles	Ethernet	✓
Formatos de compresión de video	H.264, H.264+, H.265, H.265+	Tipo de interfaz ethernet	Ethernet rápido
Formatos de audio soportados	AAC, G.711, PCM	Puertos Ethernet LAN (RJ-45)	1
Función de copia de seguridad	✓	Protocolos de red compatibles	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter ,DDNS, FTP, Alarm Server, P2P, IP Search
Detección de movimiento en video	✓	Número de usuarios	128 usuario(s)
Resoluciones de reproducción soportadas	1920×1080, 1280×1024, 1280×720	Disco duro	
Cantidad de canales	8 canales	Número de HDDs soportados	1
Color del producto *	Negro	Interfaz del HDD	SATA
Modo de reproducción	Rápido, Next, Pausa, Play, Anterior, Repetir, Barajar, Lento, Alto, Acercar	Capacidad máxima del HDD	6 TB
Señal analógica	NTSC, PAL	Control de energía	
Sistema operativo instalado	LINUX incrustado	Tipo de fuente de alimentación	CC
Contro PTZ	✓	Voltaje CD	12 V
Capacidad del rack	1U	Peso y dimensiones	
Certificación	CE: CE-LVD: EN 60950-1/IEC 60950-1 CE-EMC: EN 61000-3-2; EN 61000-3-3; EN 55032; EN 50130; EN 55024	Ancho	198 mm
Puertos e Interfaces		Profundidad	202.9 mm
puertos de entrada BNC	8	Altura	41.5 mm
puertos de salida BNC	1	Peso	620 g
Número de puertos HDMI	1	Contenido del empaque	
Puertos de salida VGA (D-Sub)	1	Cables incluidos	Corriente alterna
Entrada de audio	1	Adaptador AC incluido	✓
Salida de audio	1	Guía de configuración rápida	✓
Cantidad de puertos USB 2.0	2	Condiciones ambientales	
		Intervalo de temperatura operativa (T-T)	-10 - 45 °C
		Intervalo de temperatura de almacenaje	-20 - 70 °C

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-FEB-2024. Prints or copies of Information are only valid on the printed Publication date