

Manhattan 180894 nodo concentrador USB 3.2 Gen 1 (3.1 Gen 1) Type-A + Type-C 5000 Mbit/s Negro



Marca : Manhattan

Código del producto: 180894

Nombre del producto : 180894

Manhattan 180894. Interfaz de host: USB 3.2 Gen 1 (3.1 Gen 1) Type-A + Type-C, Interfaces de concentradores: RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A. Velocidad de transferencia de datos: 5000 Mbit/s, Color del producto: Negro, Material de la cubierta: Aluminio. Tipo de interfaz ethernet: Ethernet rápido, Gigabit Ethernet, Ethernet LAN, velocidad de transferencia de datos: 10,100,1000 Mbit/s, Estándares de red: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u. Sistemas operativos Windows soportados: Windows 10, Windows 11, Windows 7, Windows 8.1, Windows Vista, Windows XP, Otros sistemas operativos soportados: ChromeOS. Ancho: 25 mm, Profundidad: 90 mm, Altura: 19 mm

Puertos e Interfaces		Requisitos del sistema	
Interfaz de host *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A + Type-C	Sistemas operativos Windows soportados	Windows 10, Windows 11, Windows 7, Windows 8.1, Windows Vista, Windows XP
Interfaces de concentradores *	RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A	Sistemas operativos Mac soportados	✓
Cantidad de puertos tipo A USB 3.2 Gen 1 (3.1 Gen 1)	3	Sistemas operativos Linux soportados	✓
Cantidad de puertos *	4	Otros sistemas operativos soportados	ChromeOS
Características		Peso y dimensiones	
Velocidad de transferencia de datos *	5000 Mbit/s	Ancho	25 mm
Color del producto	Negro	Profundidad	90 mm
Material de la cubierta	Aluminio	Altura	19 mm
Indicadores LED	✓	Peso	57 g
Tipo de cable	Cable redondo	Empaquetado de datos	
Hot-swap	✓	Cantidad por paquete	1 pieza(s)
AWG calibre del cable	24	Peso del paquete	90 g
Longitud de cable	0.65 m	Contenido del empaque	
Certificación	CE FCC RoHS REACH UKCA	Manual	✓
Red		Condiciones ambientales	
Tipo de interfaz ethernet	Ethernet rápido, Gigabit Ethernet	Intervalo de temperatura operativa (T-T)	0 - 40 °C
Ethernet LAN, velocidad de transferencia de datos	10,100,1000 Mbit/s	Intervalo de temperatura de almacenaje	-40 - 80 °C
Estándares de red	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u	Intervalo de humedad relativa para funcionamiento	5 - 90%
Bidireccional completo (Full duplex)	✓		



0766623180894



766623180894

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.