



Dahua Technology Pro DH-HAC-HFW2249EN-A-LED 3.6MM cámara de vigilancia Bala (forma) Cámara de seguridad CCTV Interior y exterior 1920 x 1080 Píxeles Techo/pared

Marca : Dahua Technology

Familia de productos: Pro

Código del producto: DH-HAC-HFW2249EN-A-LED 3.6MM

Nombre del producto : DH-HAC-HFW2249EN-A-LED 3.6MM

Cámara Bullet Full Color 2 Megapíxeles/ Serie Pro/ Lente de 3.6 mm/ Micrófono Integrado/ FullColor-Starlight/ IP67

Dahua Technology Pro DH-HAC-HFW2249EN-A-LED 3.6MM. Tipo: Cámara de seguridad CCTV, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared, Color del producto: Blanco, Factor de forma: Bala (forma). Iluminación mínima: 0.0002 Lux, Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 89.5°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.8 mm (1 / 2.8"). Distancia de detección: 55.2 m, Distancia de observación: 22.1 m, Distancia de reconocimiento: 11 m

Performance		Video	
Type *	CCTV security camera	Maximum resolution *	1920 x 1080 pixels
Placement supported *	Indoor & outdoor	Total megapixels *	2 MP
Connectivity technology *	Wired	Supported video modes	960p, 1080p
Wide Dynamic Range (WDR)	✓	Frame rate	30 fps
Built-in light	✓	Analog signal format system	NTSC, PAL
Dynamic range	120 dB	Noise reduction	✓
Certification	CE (EN55032, EN55024, EN50130-4, EN62368-1) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)	Noise reduction technology	3D noise reduction
		Gain control type	Auto/Manual
		Back Light Compensation (BLC)	✓
		Highlight Compensation (HLC)	✓
Design		Audio	
Form factor *	Bullet	Signal-to-Noise Ratio (SNR)	65 dB
Mounting type *	Ceiling/wall	Built-in microphone	✓
Product colour *	White		
International Protection (IP) code	IP67	Network	
Camera		Ethernet LAN *	✗
Camera pan control	✗	Wi-Fi *	✗
Camera tilt control	✗	Bluetooth *	✗
Minimum illumination	0.0002 lx	Storage	
Angle of rotation	360°	Built-in HDD *	✗
Lens viewing angle, horizontal	89.5°	Ports & interfaces	
Lens viewing angle, vertical	47.3°	BNC output ports	1
Tilt angle range	0 - 90°	Power	
Pan range	0 - 360°	Power source type *	DC
White balance	Auto, Manual	Power consumption (typical)	4.2 W
Camera shutter type	Electronic	DC output voltage	12
Camera shutter speed	1/4s~1/100,000	Operational conditions	
Image sensor		Operating temperature (T-T)	-40 - 60 °C
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")	Storage temperature (T-T)	-40 - 60 °C
Progressive scan	✓	Operating relative humidity (H-H)	0 - 95%
Sensor type *	CMOS	Storage relative humidity (H-H)	0 - 95%
Lens system		Weight & dimensions	
Number of lenses *	1	Width	70 mm
Detect distance	55.2 m	Depth	70 mm
Observe distance	22.1 m	Length	179.8 mm
Recognize distance	11 m	Weight	360 g
Focal length range	2.8 - 3.6 mm		

Lens system		Packaging data	
Maximum aperture number	1	Package weight	440 g
Identify distance	5.5 m	Packaging content	
Closest focusing distance	1 m	Number of cameras *	1

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date