



Imou IPC-GK2DN-3C0W cámara de vigilancia Esférico Cámara de seguridad IP Interior 2304 x 1296 Pixeles Escritorio

Marca : Imou

Código del producto: IPC-GK2DN-3C0W

Nombre del producto : IPC-GK2DN-3C0W



Imou IPC-GK2DN-3C0W. Tipo: Cámara de seguridad IP, Colocación compatible: Interior, Tecnología de conectividad: Inalámbrico. Tipo de montaje: Escritorio, Color del producto: Negro, Factor de forma: Esférico. Ángulo de visión del objetivo, horizontal: 83°, Ángulo de visión del objetivo, vertical: 46°, Ángulo de visión de la lente, diagonal: 102°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.8 mm (1 / 2.8"). Diámetro de lente: 3.6 mm

Performance		Network	
Type *	IP security camera	Wi-Fi *	✓
Placement supported *	Indoor	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Connectivity technology *	Wireless	Bluetooth *	✗
Auto-tracking	✓	Storage	
Maximum operating distance	50 m	Built-in HDD *	✗
Design		Compatible memory cards	MicroSD (TransFlash)
Form factor *	Spherical	Maximum memory card size	256 GB
Mounting type *	Desk	Ports & interfaces	
Product colour *	Black	USB port	✓
LED indicators	✓	Security	
Camera		Built-in siren	✓
Lens viewing angle, horizontal	83°	Intelligent Video Surveillance (IVS) system features	Abnormal sound detection, Human detection
Lens viewing angle, vertical	46°	Configurable region	✓
Lens viewing angle, diagonal	102°	Management features	
Tilt angle range	0 - 90°	Reset button	✓
Pan range	0 - 355°	Power	
Image sensor		Power source type *	USB
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")	Power consumption (typical)	3.4 W
Progressive scan	✓	DC output voltage	5
Sensor type *	CMOS	DC output current	1 A
Lens system		Operational conditions	
Zoom capability	✓	Operating temperature (T-T)	-10 - 45 °C
Number of lenses *	1	Operating relative humidity (H-H)	0 - 95%
Lens diameter	3.6 mm	System requirements	
Night vision		Mobile operating systems supported	Android, iOS
Night vision *	✓	Weight & dimensions	
Night vision distance	10 m	Width	90 mm
Video		Depth	90 mm
Maximum resolution *	2304 x 1296 pixels	Height	104 mm
Total megapixels *	3 MP	Weight	206 g
Video formats supported	H.264, H.265		
Frame rate	30 fps		

Audio		Sustainability	
Built-in speaker(s)	✓	Compliance certificates	CE
Audio system	2-way	Packaging content	
Built-in microphone	✓	Number of cameras *	1
Network		Cables included	USB
Ethernet LAN *	✓	Screws included	✓

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date