

Epson Perfection V39 II Escáner de cama plana 4800 x 4800 DPI A4 Negro

Marca : Epson

Familia de productos: Perfection

Código del producto: B11B268201

Nombre del producto : V39 II

Flatbed, CIS, RGB LEDs, 4800 DPI, A4, TWAIN/ICA, USB 2.0

Epson Perfection V39 II. Tamaño máximo de escaneado: 216 x 297 mm, Resolución óptica de escáner: 4800 x 4800 DPI, Profundidad de color de entrada: 48 Bit. Tipo de escaneado: Escáner de cama plana, Color del producto: Negro, Tipo de control: Botones. Tipo de sensor: CIS, Fuentes de luz: LED RGB, Formatos de archivo para escaneo: BMP, JPEG, PDF, TIFF. Tamaño máximo de papel ISO A-series: A4, Tamaño de ISO serie A (A0...A9): A4. Tipo de fuente de alimentación: USB, Consumo energético: 2.5 W, Consumo de energía (apagado): 0.013 W



Scanning		Ports & interfaces	
Maximum scan size *	216 x 297 mm	USB port *	✓
Optical scanning resolution *	4800 x 4800 DPI	USB version	2.0
Colour scanning	✓	Power	
Duplex scanning *	✗	Power supply type *	USB
Input colour depth	48 bit	Power consumption (typical)	2.5 W
Output colour depth	24 bit	Power consumption (off)	0.013 W
Input greyscale depth	16 bit	Weight & dimensions	
Output greyscale depth	8 bit	Width	249 mm
Design		Depth	364 mm
Scanner type *	Flatbed scanner	Height	39 mm
Product colour *	Black	Weight	1.5 kg
Control type	Buttons	Packaging data	
Built-in display *	✗	Quantity per pack	1 pc(s)
Performance		Packaging content	
Sensor type *	CIS	Cables included	USB
Light source	RGB LED	System requirements	
Scan file formats	BMP, JPEG, PDF, TIFF	Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Vista, Windows XP
Button functions	Copy, On, Scan to PDF	Mac operating systems supported	Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.7.5 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Scan drivers	ICA, TWAIN		
Paper handling		Operational conditions	
Maximum ISO A-series paper size *	A4	Operating temperature (T-T)	10 - 35 °C
ISO A-series sizes (A0...A9)	A4	Storage temperature (T-T)	-20 - 60 °C
Letter	✓	Operating relative humidity (H-H)	20 - 80%
Legal	✓	Storage relative humidity (H-H)	20 - 80%

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date